STAR Standard Codes Table Interface Specification
Version 1.4.1

This specification will be in effect on 7/4/2007. STAR reserves the right to modify this specification at any time without prior consent.

Revision History Summary

| Revision Date | Effective Date | Version | Revision Description |
|---------------|----------------|---------|--|
| 1/31/2000 | 8/1/2000 | 1.0 | Initial Version |
| 7/27/2001 | 6/4/2002 | 1.1 | Add Dealer Country to IDENT record, per GM's request. Added optional generic trailer record per GM's request. |
| 3/29/2004 | 7/4/2004 | 1.2 | Draft 1.11 03/29/04 Added Reference ID (DE# 112260) to all the DTS IDENT Records per GM's (MSumner) request (UniqueRequestID 003). |
| 10/22/2004 | 7/4/2005 | 1.3 | Draft 1.21 10/22/04 - Added Sender/Destination Party Id, Location Id, and Service Id fields to IDENT per GM Canada's request MOD ID 027. Added AttributeDetail to Lineitem per GM Canada's request MOD ID 028. |
| 6/13/2005 | 7/4/2006 | 1.4 | Draft 1.31 06/13/05 -Modified the description of Interface Version (DE #100220) MODID 059. |
| 8/21/2006 | 7/4/2007 | 1.4.1 | 1.4.1 08/21/06 CR131 Ford AU - Added DE 112390 to IDENT |

File Format and Location

- * Within the context of this specification, the file format must conform to the "STAR General File Format Requirements".
- * The File name and its location must conform to the standards indicated in the "STAR" General File Format Requirements".

Record Format

* Within the context of this specification, the various record formats must conform to the "STAR General File Format" Requirements".

Record Identifiers

| Record name | Record Identifier | Comments | Add/Change/ Inactivate |
|--------------------------|-------------------|---|---------------------------|
| Identification | ST.IDENT | Must be the first record of the file. Occurs once for the entire file. | Change 1.4.1 |
| Header Information | ST.HEADER | Must be the first record of the transaction. Occurs once for each transaction. | |
| Usage Information Record | ST.USAGE | Multiple Entries of This Record Allowed | |
| Line Item Information | ST.LINEITEM | Multiple Entries of This Record Allowed | Change 1.3 |
| Trailer Information | ST.TRAILER | Optional record that must be the last record in a file. Occurs once for the entire file. Counts the number of records in the file between the IDENT record and the TRAILER record - does not count the IDENT and TRAILER. | Add 1.1 |

Identification Record Layout

| Position in Record | Data Element Definition | Data Element Name | Data Element Number | Required | Sample Data | Comments | Add/ Change/ Inactivate |
|--------------------------|--|-------------------------|---------------------------|----------|----------------|---|-------------------------------|
| 0 | Record Identifier | ST.IDENT | n/a | | ST.IDENT: | Literal as given - Must be the first record of the file. Occurs once for the entire file. | |
| 1 | DCS software creator code | Creator Name Code | 100242 | Yes | AD | | |
| 2 | DCS software code name | Creator Software Code | 100244 | Yes | "ELITE 2.0" | | |
| 3 | This is the version of the STAR data transfer specification (DTS) used to build the transaction prefaced with the CreatorNameCode. | Interface Version | 100220 | Yes | RR1.1 | | Changed 1.4 |
| 4 | Date the transaction was created | Transaction Create Date | 100430 | Yes | 19990602 | | |
| 5 | Time the transaction was created | Transaction Create Time | 100440 | Yes | 131523 | | |
| 6 | Dealer code number | Dealer Number | 100210 | Yes | 206501 | | |
| 7 | Dealer code store number (DMS assigned) | Store Number | 100240 | | 124 | | |
| 8 | Dealer code area number (DMS vendor assigned) | Area Number | 100200 | | 014 | | |
| 9 | Code for destination of file - Short Manufacturer or Short DSP code | Destination Name Code | 106190 | Yes | НО | | |
| 10 | For which software destination file is intended (May not be known) | Destination Software | 106200 | | DCS | | |
| 11 | Transaction type code indicates action to be taken for all records in this transaction set | Transaction Type Code | 106210 | | N | | |
| 12 | Dealer country location | Dealer Country | 108430 | | USA | | Add 1.1 |

Identification Record Layout

| Position in Record | Data Element Definition | Data Element Name | Data Element Number | Required | Sample Data | Comments | Add/ Change/ Inactivate |
|--------------------------|---|--------------------|---------------------------|----------|------------------------|--|-------------------------------|
| 13 | Enables the sending application to indicate the instance identifier of the event or task that caused the transaction to be created. This is used to correlate a response transaction to an originating transaction. | Reference ID | 112260 | | 12A435B | Users are not required to transmit the field unless their business partner requires it. That is, if it is on the inbound transaction, it must be put on responses to that transaction. | Add 1.2 |
| 14 | The Sender Party Id field uniquely identifies the Sender of the message. This element can be used for parties within the Automotive Community as well as external parties. Party Id is not intended as a replacement for the Dealer Number. Suggested formats for OEMs or other large institutions include: DUNs Number, ShortMfgCode + DUNs, or ShortMfgCode. The suggested format for Dealers is: ShortMfgCode+Dealer Number. | Sender Party Id | 112261 | | VW006942475 | Literal as given | Added 1.3 |
| 15 | The Sender Location Id field uniquely identifies the location of the Sender of a message. This Id may be aligned with a physical address or data centers. This field provides an additional level of granularity beyond the usage of the Party Id for additional routing and deliver of data. | Sender Location Id | 112262 | | 022360 | Literal as given | Added 1.3 |
| 16 | The Sender Service Id field identifies the particular service from which a message is being sent, e.g., an inventory service. | Sender Service Id | 112263 | | Wholesale Inventory | Literal as given | Added 1.3 |

Identification Record Layout

| Position in Record | Data Element Definition | Data Element Name | Data Element Number | Required | Sample Data | Comments | Add/ Change/ Inactivate |
|--------------------------|--|----------------------------------|---------------------------|----------|------------------------|------------------|-------------------------------|
| 17 | The Destination Party Id field uniquely identifies the Receiver of the message. This element can be used for parties within the Automotive Community as well as external parties. Party Id is not intended as a replacement for the Dealer Number. Suggested formats for OEMs or other large institutions include: DUNs Number, ShortMfgCode + DUNs, or ShortMfgCode. The suggested format for Dealers is: ShortMfgCode+Dealer Number. | Destination Party Id | 112264 | | VW401110 | Literal as given | Added 1.3 |
| 18 | The Destination Location Id field uniquely identifies the location of the Receiver of a message. This Id may be aligned with a physical address or data centers. This field provides an additional level of granularity beyond the usage of the Party Id for additional routing and deliver of data. | Destination Location Id | 112265 | | 002520 | Literal as given | Added 1.3 |
| 19 | The Destination Service Id field identifies the particular service to which a message is being sent to, e.g., an inventory service. | Destination Service Id | 112266 | | Wholesale Inventory | Literal as given | Added 1.3 |
| 20 | Identifies the version of the user's implementation of the STAR standard. For example, the user may be on their second version of a STAR Parts Order DTS 1.0. In each version of a user implementation, the user may indicate additional STAR fields that they require to receive or STAR fields that they no longer require. NOTE: This version is not that same as the Interface Version which is the STAR DTS version number used for implementation prefaced by the CreatorNameCode. | Implementation Version Number | 112390 | | 1.1 | | Added 1.4.1 |

Header Information Record Layout

| Position in Record | Data Element Definition | Data Element Name | Data Element Number | Required | Sample Data | Comments | Add/ Change/ Inactivate |
|--------------------------|---|-------------------------------------|---------------------------|----------|------------------------------------|---|-------------------------------|
| 0 | Record Identifier | ST.HEADER | n/a | | ST.HEADER: | Literal as given - Must be the first record of the transaction. Occurs once for each transaction. | |
| 1 | Effective date of standard codes table action | Standard Codes Date | 108710 | | 20000611 | | |
| 2 | Identifier of standard codes table being passed Ex: SSCDESC - Special Service Campaign Description; SSCVIN - Special Service Campaign VIN Numbers; VEHACC - Vehicle Accessory; VEHMAKE - Vehicle Make; VEHMODEL - Vehicle Model; WAREHOUSE - Parts DC | Standard Codes Table Name | 108720 | Yes | WAREHOUSE | | |
| 3 | Description of standard codes table | Standard Codes Table Description | 108730 | | "PARTS ORDER SHIP WAREHOUSE" | | |
| 4 | Type of Action for Standard Codes Table | Standard Codes Action | 108740 | Yes | N | | |

Usage Information Record Record Layout

| Position in Record | Data Element Definition | Data Element Name | Data Element Number | Required | Sample Data | Comments | Add/ Change/ Inactivate |
|--------------------------|---|------------------------------|---------------------------|----------|----------------|--|-------------------------------|
| 0 | Record Identifier | ST.USAGE | n/a | | ST.USAGE: | Literal as given - Multiple Entries of This Record Allowed | |
| 1 | Transfer interface code identifying which interface may use this standard code table. May be blank if not interface specific. | Transfer Interface Code | 108750 | | PO | | |
| 2 | AMDSG Data Element Number referencing data element utilizing this standard code table | Data Element Number Usage | 108760 | | 101450 | | |

Line Item Information Record Layout

| Position in Record | Data Element Definition | Data Element Name | Data Element Number | Required | Sample Data | Comments | Add/ Change/ Inactivate |
|--------------------------|---|---|---------------------------|----------|----------------------------|--|-------------------------------|
| 0 | Record Identifier | ST.LINEITEM | n/a | | ST.LINEITEM: | Literal as given - Multiple Entries of This Record Allowed | |
| 1 | Unique table code associated with line item description and associated values | Standard Code | 108770 | | EC1 | | |
| 2 | Description of Standard Code | Standard Code Description | 108880 | | "EAST COAST PDC" | | |
| 3 | Associated code value one | Standard Code Value One | 108890 | | 5.00 | | |
| 4 | Associated code value two | Standard Code Value Two | 108900 | | 25.75 | | |
| 5 | Supplemental code description or definition | Standard Code Supplemental Description | 108910 | | "NEW REGION" | | |
| 6 | Detail of one or many attributes. Could contain multiple comma delimited values surrounded by quotes. For example, a table row. | Attribute Detail | 112267 | | "ABC,DEF,125,2 0041103" | | Added 1.3 |

Trailer Information Record Layout

| Position in Record | Data Element Definition | Data Element Name | Data Element Number | Required | Sample Data | Comments | Add/ Change/ Inactivate |
|--------------------------|---|-------------------|---------------------------|----------|----------------|--|-------------------------------|
| 0 | Record Identifier | ST.TRAILER | n/a | | ST.TRAILER: | Literal as given - Optional record that must be the last record in a file. Occurs once for the entire file. Counts the number of records in the file between the IDENT record and the TRAILER record - does not count the IDENT and TRAILER. | Add 1.1 |
| 1 | Number of detail records contained in this file | Number of Records | 110500 | | 45 | | Add 1.1 |