

Standards for Technology in Automotive Retail

Implementation Guidelines Process Financial Statement Repository Version Rev4.5.4

Table of Contents

Overview	
Schema Field Usage	1
Business Scenario	2
Relationship Diagram	3
Schema Document Properties	
Components and Data Types	
Accountld	5
AcknowledgableVerb	
ActionExpressionCriteria	
ActionVerb	
ApplicationArea	
BusinessObjectDocument	
<u>ConfirmableVerb</u>	
Count	
<u>Destination</u>	
FinancialStatement	
FinancialStatementDetail	
<u>FinancialStatementHeader</u>	
<u>HeaderBase</u>	
<u>ld</u>	
<u>LocationId</u>	
<u>OrganizationId</u>	
Partyld	
Process	
<u>ProcessFinancialStatement</u>	
ProcessFinancialStatementDataArea	
<u>SecondaryDealerNumber</u>	
Sender	
SenderBase	
Serviceld	
Signature	
<u>Verb</u>	26

AccountingDate	2
AccountingTerm	2
AccountValue	2
<u>AcknowledgementType</u>	2
Action	2
<u>Code</u>	2
<u>ConfirmType</u>	2
Country	2 ¹
<u>DateTime</u>	4
DocumentDateTime	4
<u>Expression</u>	4
ExpressionLanguage	
FileVersionNumber	
Indicator	4
<u>Language</u>	4
Note	4
Reference	4
ReferenceNumber	
SecondaryPassword	5
ShortMfg	5
SystemVersion	5
Text	5
URI	5
s and Global Attributes	5
ApplicationArea	5
Detail	5
FinancialStatement	
Header	
Process .	5
ProcessFinancialStatement	

Process Financial Statement Guidelines

Overview

This document is a guideline on how to use the Process Financial Statement Business Object Document (BOD). Process Financial Statement has been defined in the context of STAR for the Automotive Retail Industry. The scope of this BOD is to define the Process Financial Statement process for individual consumers who service their automobiles through their OEM's authorized Dealers. The focus is on Dealer and OEM interactions, not third party organizations. NOTE: Although this is the traditional use of the Process Financial Statement, this BOD could be used to send Process Financial Statement information between any two business parties.

Implementation Guidelines provide detailed information regarding the structure and meaning of the Process Financial Statement BOD and corresponds directly to the Process Financial Statement schema. In addition to structure and meaning, the Implementation Guidelines identify various business rules for specific fields/components that due to their nature, i.e. field interdependence, are not possible to express using schema. Please note that although these business rules are not included in the schema, they <u>MUST</u> be followed to be STAR Compliant. Therefore, the Process Financial Statement Implementation Guidelines must be used in concert with the Process Financial Statement schema during development and should <u>NOT</u> be considered a supplement or substitution to the schema. For more information regarding STAR XML Data Compliance, please review the STAR Data Compliance Guidelines document located on the STAR Web site.

For a copy of the corresponding Process Financial Statement schema, please download the appropriate STAR schema repository from the XML portion of the STAR website (www.starstandard.org). Prior to downloading the schema, users are encouraged to download the STAR XML Reference/Implementation document also located on the XML portion of the STAR website. This document provides an overview of the STAR BOD development methodology, how to download and read STAR schema, and various frequently asked questions related to the implementation of STAR BODs.

STAR has followed the Open Application Group's Business Object Document methodology to develop the Process Financial Statement BOD. Where possible, STAR has mapped to existing OAGI fields and components. Note however that the STAR Process Financial Statement BOD is unique to the Retail Automotive industry and is not an extension of any existing OAGIS BODs.

For more information on the Open Applications Group's BODs and related documentation please refer to the Open Applications Group's Web site at (www.openapplications.org).

Schema Field Usage


STAR uses the same Noun in the schema for all the Noun/Verb combinations of the Process Financial Statement except the Get verb. Please refer to each Noun/Verb combination within this document to understand the requirements for each specific BOD. Although the Noun will always have every field defined for the Noun in the schema, each Noun/Verb combination may not use all of the fields. If a field is not used by a BOD, it will be noted in the business rules.

Business Scenario

BUSINESS SCENARIO MISSING. Please make sure it is defined in the build script.

Relationship Diagram

The following is a representation of the Noun for this BOD. It is a high level overview provided to give an idea of the hierarchy of the Noun's components.



Schema Document Properties

Declared Namespaces

A schema can contain more than one namespace. According to Whatis.com, "In general, a namespace uniquely identifies a set of names so that there is no ambiguity when objects having different origins but the same names are mixed together." An example would be two namespaces that both defined an element called ID, without a namespace it would be impossible to determine which definition was being used.

Prefix	Namespace
Default namespace	http://www.starstandards.org/STAR
xml	http://www.w3.org/XML/1998/namespace
xsd	http://www.w3.org/2001/XMLSchema

Components and Data Types

Global definitions include components, code lists, and data types. Components are used to build the data structures that make up a Noun and it's requirements. Data types specify the type of data that a component's fields may contain. Not all definitions are included in this documentation. Please see either the STAR Code List guideline or Data Type Guidelines for further information.

AccountId

These field(s) use this type: **AccountId.**

Identifies an account number or similary identifier.

Name	AccountId
Abstract	no

XML Instance Representation



AcknowledgableVerb

Name	AcknowledgableVerb
Abstract	yes

Attributes

Field / Component	Description	R/O	Business Rule
acknowledge		R	

Field / Component	Description	R/O	Business Rule
Verb		R	
Criteria		О	

XML Instance Representation

ActionExpressionCriteria

These field(s) use this type: **Criteria.**

Name	ActionExpressionCriteria
Abstract	no

Attributes

Field / Component	Description	R/O	Business Rule
expressionLanguage		R	

Data Elements and Components

Field / Component	Description	R/O	Business Rule
Expression		R	

XML Instance Representation

```
<...
expressionLanguage="ExpressionLanguage [0..1]">
    <Expression> ... </Expression> [1..*]
```

</...>

ActionVerb

Name	ActionVerb
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
Verb		R	
Criteria		O	

XML Instance Representation

ApplicationArea

These field(s) use this type: **ApplicationArea.**

Name	ApplicationArea
Abstract	no

Field / Component	Description	R/O	Business Rule
Sender	Identifies characteristics and control identifiers that relate to the application that created the Business Object Document. The sender area can indicate the logical location of the application and/or database server the application, and the task that was processing to create the BOD.	R ·,	

Field / Component	Description R/	/0	Business Rule
CreationDateTime	is the date time stamp that the given instance of the Business Object R Document was created. This date must not be modified during the life of the Business Object Document.		DateTime fields must be formatted as XML Schema Datetimes in UTC/GMT format without offsets. Example: 2003-11-05T13:15:30Z
Signature	If the BOD is to be signed the signature element is included, otherwise it O is not. Signature supports any digital signature that maybe used by an implementation of OAGIS. The qualifying Agency identifies the agency that provided the format for the signature. This element supports any digital signature specification that is available today and in the future. This is accomplished by not actually defining the content but by allowing the implementation to specify the digital signature to be used via an external XML Schema namespace declaration. The Signature element is defined to have any content from any other namespace. This allows the user to carry a digital signature in the xml instance of a BOD. The choice of which digital signature to use is left up to the user and their integration needs.)	Optional. "qualifyingAgency" attribute.
BODId	The BODId provides a place to carry a Globally Unique Identifier O (GUID) that will make each Business Object Document instance uniquely identifiable. This is a critical success factor to enable software developers to use the Globally Unique Identifier (GUID) to build the following services or capabilities: 1. Legally binding transactions, 2. Transaction logging, 3. Exception handling, 4. Re-sending, 5. Reporting, 6. Confirmations, 7. Security.)	
Destination	Information related to the receiver of the BOD R		See Destination Component.

XML Instance Representation

```
<...>
<Sender> Sender </Sender> [1]
<CreationDateTime> DateTime </CreationDateTime> [1]
<Signature> Signature </Signature> [0..1]
<BODId> Code </BODId> [0..1]
<Destination> Destination </Destination> [1]
</...>
```

BusinessObjectDocument

Name	BusinessObjectDocument
Abstract	no

Attributes

Field / Component	Description	R/O	Business Rule
revision	This should contain the STAR repository version in the following recommended format. 4.2.1_M20080416. Where the first part indicates the version of the STAR repository and anything after the _ indicates the Milestone build that is being used. If referring to an official published version then only the STAR Repository version is required.	0	
release	Indicates the OAGIS release that this BOD belongs.	О	
environment	Indicates whether this BOD is being sent in a "Test" or a "Production" mode. If the BOD is being sent in a test mode, it's information should no affect the business operation. However, if the BOD is sent in "Production" mode it is assumed that all test has been complete and the contents of the BOD are to affect the operation of the receiving business application(s).		
lang	Indicates the language that the contents of the BOD is in unless otherwise stated.	0	
bodVersion	Deprecated as of STAR 4.2.2. It is recommended to use the revision attribute to identify the repository and the noun. May be removed in a new major version of the STAR repository. Indicates the version numbe of the BOD.	O r	

Field / Component	Description	R/O	Business Rule
ApplicationArea	Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of. Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.		

XML Instance Representation

ConfirmableVerb

Name	ConfirmableVerb
Abstract	no

Attributes

Field / Component	Description	R/O	Business Rule
confirm		R	

Field / Component	Description	R/O	Business Rule
Verb		R	

XML Instance Representation

<...

confirm="ConfirmType [0..1]"/>

Count

These field(s) use this type: **Count.**

Simple quantity type with no attributes

Name	Count
Abstract	no

XML Instance Representation

<...>
xsd:integer
</...>

Destination

These field(s) use this type: **Destination.**

Name	Destination
Abstract	no

Field / Component	Description	R/O	Business Rule
DestinationNameCode	Code for destination of file (i.e.Short Manufacturer or DSP code)	O	Must use a valid code from the ShortMfg/RSP list on http://www.starstandards.org

Field / Component	Description	R/O	Business Rule
DestinationURI	Physical address of the destination	О	
DestinationSoftwareCode	Additional information about the destination application	О	
DestinationSoftware	For which software destination file is intended (may not be known).	О	
DealerNumber	Target Dealer Code receiving information	О	
StoreNumber	Dealer code store number (DMS assigned)	О	
AreaNumber	Dealer code area number (DMS vendor assigned)	О	
DealerCountry	Target Dealer country location	О	
PartyId	The Party Id field uniquely identifies the Receiver of the message. This element can be used for parties within the Automotive Community as well as external parties. Party Id is not intended as a replacement for the Dealer Number. Suggested formats for OEMs or other large institutions include: DUNs Number, ShortMfgCode + DUNs, or ShortMfgCode. The suggested format for Dealers is: ShortMfgCode+Dealer Number.		
LocationId	The Location Id field uniquely identifies the location of the Receiver of message. This Id may be aligned with a physical address or data centers. This field provides an additional level of granularity beyond the usage of the Party Id for additional routing and deliver of data.		
ServiceId	The Service Id field identifies the particular service to which a message is being sent, e.g., an inventory service.	0	

XML Instance Representation

```
<PartyId> PartyId </PartyId> [0..1]
<LocationId> LocationId </LocationId> [0..1]
<ServiceId> ServiceId </ServiceId> [0..1]
</...>
```

FinancialStatement

These field(s) use this type: **FinancialStatement.**

STAR Version 3.0 - Draft

STAR Version 2.1, STAR approved 04/20/2005; effective date 07/04/2005

STAR Version 2.0, STAR approved 05/07/2004; effective date 07/04/2004

STAR Version 1.0, STAR approved 10/4/2002; OAGI approved 10/17/2002; effective date 1/01/2003

Name	FinancialStatement
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
Header		R	
Detail		R	

XML Instance Representation

```
<...>
    <Header> ... </Header> [1]
    <Detail> ... </Detail> [1..*]
    </...>
```

FinancialStatementDetail

These field(s) use this type: **<u>Detail.</u>**

.

Name	FinancialStatementDetail
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
AccountId	Unique identifier that defines the account being reported on	R	
AccountValue	Reported Account Value or Literal	R	

XML Instance Representation

```
<...>
    <AccountId> AccountId </AccountId> [1]
    <AccountValue> AccountValue </AccountValue> [1]
    </...>
```

FinancialStatementHeader

These field(s) use this type: **Header.**

Name	FinancialStatementHeader
Abstract	no

Field / Component	Description	R/O	Business Rule
DocumentDateTime	Is the date and time the document was last created. This is not the date and time that the BOD message instance was created.	0	DateTime fields must be formatted as XML Schema DateTimes in UTC/GMT format without offsets. Example: 2003-11-05T13:15:30Z
SecondaryPassword	Secondary password used to validate access to the dealer information	О	(INACTIVE)

Field / Component	Description	R/O	Business Rule
SecondaryDealerNumber	Identifies secondary dealer number if different than primary "Dealer Number"	О	(INACTIVE)
AccountingDate	Reporting period for financial statement (i.e., year and month)	R	
AccountingTerm	Term of Account Information	O	
Count	Number of detail components contained in this transaction	O	
FileVersionNumber	Indicates the verion of validation performed on the Data	O	
OrganizationId	Member Identification number of affiliate organization. Ex: NADA 20 Group code	О	

XML Instance Representation

HeaderBase

Used on all STAR BODs

Name	HeaderBase
Abstract	no

Field / Component	Description	R/O	Business Rule
DocumentDateTime	Is the date and time the document was last created. This is not the date and time that the BOD message instance was created.	0	DateTime fields must be formatted as XML Schema DateTimes in UTC/GMT format without offsets. Example: 2003-11-05T13:15:30Z
SecondaryPassword	Secondary password used to validate access to the dealer information	О	(INACTIVE)
SecondaryDealerNumber	Identifies secondary dealer number if different than primary "Dealer Number"	О	(INACTIVE)

XML Instance Representation

```
<...>
    <br/>
    <br/>
```

ld

These field(s) use this type: **AuthorizationId.**

Party Identification number

Name	ld .
Abstract	no

XML Instance Representation



LocationId

These field(s) use this type: **LocationId**, **LocationId**.

Code identifying a physical location

Name LocationId

Abstract no

XML Instance Representation

<...> Id </...>

OrganizationId

These field(s) use this type: **OrganizationId.**

Member Identification number of affiliate organization

Name OrganizationId

Abstract no

XML Instance Representation

<...> Id </...>

Partyld

These field(s) use this type: **<u>DealerNumber,PartyId,DealerNumber,PartyId.</u>**

Party Identification Number

Name Partyld

Abstract no

XML Instance Representation

<...>

Id </...>

Process

These field(s) use this type: **Process.**

Name	Process
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
Verb		R	
Criteria		О	

XML Instance Representation

ProcessFinancialStatement

These field(s) use this type: **ProcessFinancialStatement.**

Name	ProcessFinancialStatement
Abstract	no

Field / Component	Description	R/O	Business Rule
ApplicationArea	Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of. Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.	2	
DataArea		R	

XML Instance Representation

ProcessFinancialStatementDataArea

These field(s) use this type: **DataArea.**

Name	ProcessFinancialStatementDataArea
Abstract	no

Field / Component	Description	R/O	Business Rule
Process	The Process verb is used to request processing of the associated no the receiving application or business to party. In a typical external exchange scenario a Process BOD is considered to be a legally bin message. For example, if a customer sends a ProcessPurchaseOrde to a supplier and the supplier acknowlegdes with a positive AcknowledgePurchaseOrder, then the customer is obligated to full agreement, unless of course other BODs are allowed to cancel or c the original order.	ding r BOD fil the	
FinancialStatement		R	

XML Instance Representation

```
<...>
<Process> ... </Process> [1]
<FinancialStatement> ... </FinancialStatement> [1..*]
</...>
```

SecondaryDealerNumber

These field(s) use this type: **SecondaryDealerNumber.**

Identifies secondary dealer number if different than primary "Dealer Number"

Name	SecondaryDealerNumber
Abstract	no

XML Instance Representation



Sender

These field(s) use this type: **Sender.**

Name	Sender
Abstract	no

Field / Component	Description	R/O	Business Rule
LogicalId	Provides the logical location of the server and applications from we the Business Object Document originated. It can be used to establi logical to physical mapping, however its use is optional. Each syst combination of systems should maintain an external central referentable containing the logical names or logical addresses of the applications in the integration configuration. This enables the logical not be mapped to the physical network addresses of the resources not the network. Note: The technical implementation of this Domai Naming Service is not dictated by this specification. This logical to physical mapping may be done at execution time by the application or by a middleware transport mechanism, depending on the integral architecture used. This provides for a simple but effective director access capability while maintaining application independence from physical location of those resources on the network	sh a em or nce lecation lames leeded in o n itself ation	
Component	Provides a finer level of control than Logical Identifier and represe business application that issued the Business Object Document. Its optional. For STAR's use this is the DCS Software code name		
Task	Describes the business event that initiated the need for the Busines Object Document to be created. For STAR, the task is defined in t Implementation Guidelines for each BOD. It is usually a short description of the BOD. Ex: SalesLead, CreditDecision, etc.		
ReferenceId	Enables the sending application to indicate the instance identifier of event or task that caused the BOD to be created. This is used to coa response BOD to an originating BOD		
AuthorizationId	Identifyies the authorization level of the user or application that is sending the Business Object Document Message. This authorization being recognized be the receiving system indicates what can be do the receiving system. For STAR, this is the User ID.	on level	
CreatorNameCode	DCS Software Creator Code	R	

Field / Component	Description	R/O	Business Rule
SenderNameCode	Additional information about the sending platform (i.e., Short MFG or DSP code).	R	Must use a valid code from the ShortMfg/RSP list on http://www.starstandards.org
SenderURI	Physical address of the sender	О	
DealerNumber	Dealer Code of source of information	O	Dealer Number is Required if originating from DMS.
StoreNumber	Dealer code store number (DMS assigned)	О	
AreaNumber	Dealer code area number (DMS vendor assigned)	О	
DealerCountry	Source Dealer country location	O	Reference Country enumerator.
Language	This code is used to define the language of the data used in this transaction	0	Reference Language enumerator.
DeliverPendingMailInd	Indicates if the user requests to receive pending mail that has been store and has yet not been delivered yet. By selecting 0, the user will only receive the response for the current transaction the user is performing.	d O	1 - Receive Pending Mail. 0 - Do not receive pending mail.
Password	Token for application specific authentication. Used to authenticate dealership/users through application specific security	0	
SystemVersion	The sender's software version number.	О	
PartyId	The Party Id field uniquely identifies the Sender of the message. This element can be used for parties within the Automotive Community as well as external parties. Party Id is not intended as a replacement for the Dealer Number. Suggested formats for OEMs or other large institutions include: DUNs Number, ShortMfgCode + DUNs, or ShortMfgCode. The suggested format for Dealers is: ShortMfgCode+Dealer Number.		
LocationId	The Location Id field uniquely identifies the location of the Sender of a message. This Id may be aligned with a physical address or data centers. This field provides an additional level of granularity beyond the usage of the Party Id for additional routing and deliver of data.		

Field / Component	Description	R/O	Business Rule
ServiceId	The Service Id field identifies the particular service from which a message is being sent, e.g., an inventory service.	О	

XML Instance Representation

```
<...>
 <LogicalId> Text </LogicalId> [0..1]
 <Component> Text </Component> [1]
 <Task> Text </Task> [1]
 <ReferenceId> Reference </ReferenceId> [0..1]
 < AuthorizationId > Id < / AuthorizationId > [0..1]
 <CreatorNameCode> Text </CreatorNameCode> [1]
 <SenderNameCode> ShortMfg </SenderNameCode> [1]
 <SenderURI> URI </SenderURI> [0..1]
 <DealerNumber> PartyId 
PartyId 
[0..1]
 <StoreNumber> Text </StoreNumber> [0..1]
 <AreaNumber> Text </AreaNumber> [0..1]
 <DealerCountry> Country /DealerCountry> [0..1]
 <Language> Language </Language> [0..1]
 <DeliverPendingMailInd> Indicator </DeliverPendingMailInd> [0..1]
 <Password> Text </Password> [0..1]
 <SystemVersion> SystemVersion </SystemVersion> [0..1]
 <PartyId> PartyId </PartyId> [0..1]
 <LocationId> LocationId </LocationId> [0..1]
 <ServiceId> ServiceId </ServiceId> [0..1]
</...>
```

SenderBase

Name	SenderBase SenderBase
Abstract	no no

Field / Component	Description	R/O	Business Rule
LogicalId	Provides the logical location of the server and applications from which the Business Object Document originated. It can be used to establish a logical to physical mapping, however its use is optional. Each system or combination of systems should maintain an external central reference table containing the logical names or logical addresses of the application systems in the integration configuration. This enables the logical names to be mapped to the physical network addresses of the resources needed on the network. Note: The technical implementation of this Domain Naming Service is not dictated by this specification. This logical to physical mapping may be done at execution time by the application itsel or by a middleware transport mechanism, depending on the integration architecture used. This provides for a simple but effective directory access capability while maintaining application independence from the physical location of those resources on the network	1	
Component	Provides a finer level of control than Logical Identifier and represents the business application that issued the Business Object Document. Its use it optional. For STAR's use this is the DCS Software code name		
Task	Describes the business event that initiated the need for the Business Object Document to be created. For STAR, the task is defined in the Implementation Guidelines for each BOD. It is usually a short description of the BOD. Ex: SalesLead, CreditDecision, etc.	R	
ReferenceId	Enables the sending application to indicate the instance identifier of the event or task that caused the BOD to be created. This is used to correlate a response BOD to an originating BOD		
AuthorizationId	Identifyies the authorization level of the user or application that is sending the Business Object Document Message. This authorization level being recognized be the receiving system indicates what can be done on the receiving system. For STAR, this is the User ID.		

XML Instance Representation

```
<...>
<LogicalId> Text </LogicalId> [0..1]
<Component> Text </Component> [1]
<Task> Text </Task> [1]
```

<ReferenceId> Reference </ReferenceId> [0..1]
<AuthorizationId> Id </AuthorizationId> [0..1]
</...>

ServiceId

These field(s) use this type: **ServiceId**, **ServiceId**.

The Service Id field identifies the particular service to or from which a message is being sent, e.g., an inventory service.

Nam	e	Serviceld
Abst	ract	no

XML Instance Representation



Signature

These field(s) use this type: **Signature.**

Name	Signature
Abstract	no

Attributes

Field / Component	Description	R/O	Business Rule
qualifyingAgency		О	

XML Instance Representation

```
<...
qualifyingAgency="Text [0..1]">
Allow any elements from any namespace (strict validation). [0..1]
</...>
```

Verb

These field(s) use this type: **Verb.**

Name	Verb
Abstract	no

Data Elements and Components

XML Instance Representation

<.../>

Accounting Date

These field(s) use this type: **AccountingDate.**

Month and year accounting date conforms to ISO 8601 format rules Ex: $\d\d\d\d\d$

Name Accounting Date

Base XSD Type: gYearMonth

AccountingTerm

These field(s) use this type: **AccountingTerm.**

Term of Account Information

Name	AccountingTerm	
Base XSD Type: string		
Code Value	Description	
MTD	Month To Date	
YTD	Year To Date	

AccountValue

These field(s) use this type: **AccountValue.**

Reported Account Value or Literal.

Name AccountValue

Base XSD Type: string

AcknowledgementType

Name	AcknowledgementType		
Base XSD Type: NMTOKEN	Base XSD Type: NMTOKEN		
Code Value	Description		
Always			
OnChange			
Never			

Action

Name

Base XSD Type: string

2 doo / to 2 .) por our ing	
Code Value	Description
Add Delete Change Replace	
Delete	
Change	
Replace	
A	
D	
C	
R	

Code

These field(s) use this type: $\underline{\textbf{BODId.}}$

Unique code name

Name Code

Base XSD Type: string

ConfirmType

Name	ConfirmType			
Base XSD Type: NMTOKEN				
Code Value	Description			
Always				

Code Value	Description
OnChange	
Never	

Country

These field(s) use this type: **DealerCountry**, **DealerCountry**.

Country in which the Address is in. Conforms to ISO 3166-2. AF -AFGHANISTAN AL -ALBANIA DZ -ALGERIA AS -AMERICAN SAMOA AD -ANDORRA AO -ANGOLA AI -ANGUILLA AQ -ANTARCTICA AG -ANTIGUA AND BARBUDA AR -ARGENTINA AM -ARMENIA AW -ARUBA AU -AUSTRALIA AT -AUSTRIA AZ -AZERBAIJAN BS -BAHAMAS BH -BAHRAIN BD -BANGLADESH BB -BARBADOS BY -BELARUS BE -BELGIUM BZ -BELIZE BJ -BENIN BM -BERMUDA BT -BHUTAN BO -BOLIVIA BA -BOSNIA AND HERZEGOVINA BW -BOTSWANA BV -BOUVET ISLAND BR -BRAZIL IO-BRITISH INDIAN OCEAN TERRITORY BN -BRUNEI DARUSSALAM BG -BULGARIA BF-BURKINA FASO BI-BURUNDI KH-CAMBODIA CM-CAMEROON CA-CANADA CV-CAPE VERDE KY-CAYMAN ISLANDS CF -CENTRAL AFRICAN REPUBLIC TD -CHAD CL -CHILE CN -CHINA CX -CHRISTMAS ISLAND CC -COCOS (KEELING) ISLANDS CO -COLOMBIA KM -COMOROS CG -CONGO CD -CONGO. THE DEMOCRATIC REPUBLIC OF THE CK -COOK ISLANDS CR -COSTA RICA CI -CÃ#Â#TE D'IVOIRE HR -CROATIA CU -CUBA CY -CYPRUS CZ -CZECH REPUBLIC DK -DENMARK DJ -DJIBOUTI DM -DOMINICA DO -DOMINICAN REPUBLIC EC -ECUADOR EG -EGYPT SV -EL SALVADOR GO -EOUATORIAL GUINEA ER -ERITREA EE -ESTONIA ET -ETHIOPIA FK -FALKLAND ISLANDS (MALVINAS) FO -FAROE ISLANDS FJ -FIJI FI -FINLAND FR -FRANCE GF -FRENCH GUIANA PF -FRENCH POLYNESIA TF -FRENCH SOUTHERN TERRITORIES GA -GABON GM -GAMBIA GE -GEORGIA DE -GERMANY GH -GHANA GI -GIBRALTAR GR -GREECE GL -GREENLAND GD -GRENADA GP -GUADELOUPE GU -GUAM GT -GUATEMALA GN -GUINEA GW -GUINEA-BISSAU GY -GUYANA HT -HAITI HM -HEARD ISLAND AND MCDONALD ISLANDS VA -HOLY SEE (VATICAN CITY STATE) HN -HONDURAS HK -HONG KONG HU -HUNGARY IS -ICELAND IN -INDIA ID -INDONESIA IR -IRAN, ISLAMIC REPUBLIC OF IQ -IRAQ IE -IRELAND IL -ISRAEL IT -ITALY JM -JAMAICA JP -JAPAN JO -JORDAN KZ -KAZAKHSTAN KE -KENYA KI -KIRIBATI KP -KOREA. DEMOCRATIC PEOPLE'S REPUBLIC OF KR -KOREA, REPUBLIC OF KW -KUWAIT KG -KYRGYZSTAN LA -LAO PEOPLE'S DEMOCRATIC REPUBLIC LV -LATVIA LB -LEBANON LS -LESOTHO LR -LIBERIA LY -LIBYAN ARAB JAMAHIRIYA LI -LIECHTENSTEIN LT -LITHUANIA LU -LUXEMBOURG MO -MACAO MK -MACEDONIA, THE FORMER YUGOSLAV REPUBLIC OF MG -MADAGASCAR MW -MALAWI MY -MALAYSIA MV -MALDIVES ML -MALI MT -MALTA MH -MARSHALL ISLANDS MO -MARTINIQUE MR -MAURITANIA MU -MAURITIUS YT -MAYOTTE MX -MEXICO FM -MICRONESIA, FEDERATED STATES OF MD -MOLDOVA, REPUBLIC OF MC -MONACO MN -MONGOLIA MS -MONTSERRAT MA -MOROCCO MZ -MOZAMBIOUE MM -MYANMAR NA -NAMIBIA NR -NAURU NP -NEPAL NL -NETHERLANDS AN -NETHERLANDS ANTILLES NC -NEW CALEDONIA NZ -NEW ZEALAND NI -NICARAGUA NE -NIGER NG -NIGERIA NU -NIUE NF -NORFOLK ISLAND MP -NORTHERN MARIANA ISLANDS NO -NORWAY OM -OMAN PK -PAKISTAN PW -PALAU PS -PALESTINIAN TERRITORY, OCCUPIED PA -PANAMA PG -PAPUA NEW GUINEA PY -PARAGUAY PE -PERU PH -PHILIPPINES PN -PITCAIRN PL -POLAND PT -PORTUGAL PR -PUERTO RICO OA -OATAR RE -RÃ#Â#UNION RO -ROMANIA RU -RUSSIAN FEDERATION RW -RWANDA SH -SAINT HELENA KN -SAINT KITTS AND NEVIS LC -SAINT LUCIA PM -SAINT PIERRE AND MIQUELON

VC -SAINT VINCENT AND THE GRENADINES WS -SAMOA SM -SAN MARINO ST -SAO TOME AND PRINCIPE SA -SAUDI ARABIA SN -SENEGAL CS -SERBIA AND MONTENEGRO SC -SEYCHELLES SL -SIERRA LEONE SG -SINGAPORE SK -SLOVAKIA SI -SLOVENIA SB -SOLOMON ISLANDS SO -SOMALIA ZA -SOUTH AFRICA GS -SOUTH GEORGIA AND THE SOUTH SANDWICH ISLANDS ES -SPAIN LK -SRI LANKA SD -SUDAN SR -SURINAME SJ -SVALBARD AND JAN MAYEN SZ -SWAZILAND SE -SWEDEN CH -SWITZERLAND SY -SYRIAN ARAB REPUBLIC TW -TAIWAN, PROVINCE OF CHINA TJ -TAJIKISTAN TZ -TANZANIA, UNITED REPUBLIC OF TH -THAILAND TL -TIMOR-LESTE TG - TOGO TK -TOKELAU TO -TONGA TT -TRINIDAD AND TOBAGO TN -TUNISIA TR -TURKEY TM -TURKMENISTAN TC -TURKS AND CAICOS ISLANDS TV -TUVALU UG -UGANDA UA -UKRAINE AE -UNITED ARAB EMIRATES GB -UNITED KINGDOM US -UNITED STATES UM -UNITED STATES MINOR OUTLYING ISLANDS UY -URUGUAY UZ -UZBEKISTAN VU -VANUATU VE -VENEZUELA VN -VIET NAM VG -VIRGIN ISLANDS, BRITISH VI -VIRGIN ISLANDS, U.S. WF -WALLIS AND FUTUNA EH -WESTERN SAHARA YE -YEMEN ZM -ZAMBIA ZW -ZIMBABWE

Name	Country		
Base XSD Type: strii	ng		
Code Value		Description	
US			
AF			
AL			
DZ			
AS			
AD			
AO			
AI			
AQ			
AG			
AR			
AM			
AW			
AU	Tarker la maio Automatica Datail 6		

Code Value	Description
AT	
AZ	
BS	
вн	
BD	
BB	
BY	
BE	
BZ	
ВЈ	
BM	
BT	
ВО	
BA	
BW	
BV	
BR	
IO	
BN	
BG	
BF	
BI	

Code Value	Description
KH	
CM	
CA	
CV	
KY	
CF	
TD	
CL	
CN	
CX	
CC	
СО	
KM	
CG	
CD	
CK	
CR	
CI	
HR	
CU	
CY	
CZ	

Code Value	Description
DK	
DJ	
DM	
DO	
EC	
EG	
SV	
GQ	
ER	
EE	
ET	
FK	
FO	
FJ	
FI	
FR	
GF	
PF	
TF	
GA	
GM	
GE	

Code Value	Description
DE	
GH	
GI	
GR	
GL	
GD	
GP	
GU	
GT	
GN	
GW	
GY	
HT	
HM	
VA	
HN	
НК	
HU	
IS	
IN	
ID	
IR	

Code Value	Description
IQ	
IE	
IL	
IT	
JM	
JP	
lO	
KZ	
KE	
KI	
KP	
KR	
KW	
KG	
LA	
LV	
LB	
LS	
LR	
LY	
LI	
LT	

Code Value	Description
LU	
MO	
MK	
MG	
MW	
MY	
MV	
ML	
MT	
MH	
MQ	
MR	
MU	
YT	
MX	
FM	
MD	
MC	
MN	
MS	
MA	
MZ	

Code Value	Description
MM	
NA	
NR	
NP	
NL	
AN	
NC	
NZ	
NI	
NE	
NG	
NU	
NF	
MP	
NO	
OM	
PK	
PW	
PS	
PA	
PG	
PY	

Code Value	Description
PE	
РН	
PN	
PL	
PT	
PR	
QA	
RE	
RO	
RU	
RW	
SH	
KN	
LC	
PM	
VC	
WS	
SM	
ST	
SA	
SN	
CS	

Code Value	Description
SC	
SL	
SG	
SK	
SI	
SB	
SO	
ZA	
GS	
ES	
LK	
SD	
SR	
SJ	
SZ	
SE	
СН	
SY	
TW	
ТЈ	
TZ	
TH	

Code Value	Description
TL	
TG	
TK	
ТО	
TT	
TN	
TR	
TM	
TC	
TV	
UG	
UA	
AE	
GB	
UM	
UY	
UZ	
VU	
VE	
VN	
VG	
VI	

Code Value	Description	
WF		
ЕН		
YE		
ZM		
ZW		

DateTime

These field(s) use this type: **CreationDateTime.**

Date and time conforms to ISO 8601 format rules without offset EX:2003-11-05T13:15:30Z

Name DateTime

Base XSD Type: dateTime

DocumentDateTime

These field(s) use this type: **<u>DocumentDateTime.</u>**

Is the date and time the document was last created. This is not the date and time that the BOD message instance was created.

Name DocumentDateTime

Base XSD Type: dateTime

Expression

Name	Expression

Base XSD Type: string

ExpressionLanguage

Name ExpressionLanguage

Base XSD Type: string

FileVersionNumber

These field(s) use this type: **FileVersionNumber.**

Indicates the version of validation performed on the data

Name FileVersionNumber

Base XSD Type: string

Indicator

These field(s) use this type: **DeliverPendingMailInd.**

0 = No, 1 = Yes

Name	Indicator
Base XSD Type: string	
Code Value	Description
0	
1	

Language

These field(s) use this type: **Language.**

Language conforms to ISO 639-2 rules. Note the format for this field is language-Country (see Country data type for the list of countries with definitions). AA "Afar", AB "Abkhazian", AF "Afrikaans", AM "Amharic", AR "Arabic", AS "Assamese", AY "Aymara", AZ "Azerbaijani", BA "Bashkir", BE

"Byelorussian", BG "Bulgarian", BH "Bihari", BI "Bislama", BN "Bengali" "Bangla", BO "Tibetan", BR "Breton", CA "Catalan", CO "Corsican", CS "Czech", CY "Welsh", DA "Danish", DE "German", DZ "Bhutani", EL "Greek", EN "English" "American", ES "Spanish", ET "Estonian", EU "Basque", FA "Persian", FI "Finnish", FJ "Fiji", FO "Faeroese", FR "French", FY "Frisian", GA "Irish", GD "Gaelic" "Scots Gaelic", GL "Galician", GN "Guarani", GU "Gujarati", HA "Hausa", HI "Hindi", HR "Croatian", HU "Hungarian", HY "Armenian", IK "Inupiak", IN "Indonesian", IS "Icelandic", IT "Italian", IW "Hebrew", JA "Japanese", JI "Yiddish", JW "Javanese", KA "Georgian", KK "Kazakh", KL "Greenlandic", KM "Cambodian", KN "Kannada", KO "Korean", KS "Kashmiri", KU "Kurdish", KY "Kirghiz", LA "Latin", LN "Lingala", LO "Laothian", LT "Lithuanian", LV "Latvian" "Lettish", MG "Malagasy". MI "Maori", MK "Macedonian", ML "Malayalam", MN "Mongolian", MO "Moldavian", MR "Marathi", MS "Malay", MT "Maltese", MY "Burmese", NA "Nauru", NE "Nepali", NL "Dutch", NO "Norwegian", OC "Occitan", OM "Oromo" "Afan", OR "Oriya", PA "Punjabi", PL "Polish", PS "Pashto" "Pushto", PT "Portuguese", QU "Quechua", RM "Rhaeto-Romance", RN "Kirundi", RO "Romanian", RU "Russian", RW "Kinyarwanda", SA "Sanskrit", SD "Sindhi", SG "Sangro", SH "Serbo-Croatian", SI "Singhalese", SK "Slovak", SL "Slovenian", SM "Samoan", SN "Shona", SO "Somali", SQ "Albanian", SR "Serbian", SS "Siswati", ST "Sesotho", SU "Sudanese", SV "Swedish", SW "Swahili", TA "Tamil", TE "Tegulu", TG "Tajik", TH "Thai", TI "Tigrinya", TK "Turkmen", TL "Tagalog", TN "Setswana", TO "Tonga", TR "Turkish", TS "Tsonga", TT "Tatar", TW "Twi", UK "Ukrainian", UR "Urdu", UZ "Uzbek", VI "Vietnamese", WO "Wolof", XH "Xhosa", YO "Yoruba", ZH "Chinese", ZU "Zulu"

Name	Language
Base XSD Type: string	
Code Value	Description
en-US	
en-CA	
aa-ET	
ab-GE	
af-ZA	
am- ET	
ar-SA	
as-IN	
ay-BO	
az-AZ	
ba-RU	
be-BY	

Description
Везеприон

Description
Description

Code Value	Description
kl-GL	
km-KH	
kn-IN	
ko-KP	
ko-KR	
ks-IN	
ku-IQ	
ky-CN	
la-VA	
ln-CD	
lo-LA	
lt-LT	
lv-LV	
mg-MG	
mi-NZ	
mk-MK	
ml-IN	
mn-MN	
mo-MO	
mr-IN	
ms-MY	
mt-MH	

Code Value	Description	
my-MM		
na-NR		
ne-NP		
nl-NL		
no-NO		
oc-FR		
om- ET		
or-IN		
pa-IN		
pl-PL		
ps-PK		
pt-PT		
qu-PE		
rm-CH		
rn-BI		
ro-RO		
ru-RU		
rw-RW		
sa-IN		
sd-PK		
sg-CF		
sh-HR		

Code Value	Description
si-LK	
sk-SK	
sl-SI	
sm-WS	
sn-ZW	
so-SO	
sq-AL	
sr-CS	
ss-ZA	
st-ZA	
su-SD	
sv-SE	
sw-TL	
ta-IN	
te-IN	
tg-TJ	
th-TH	
ti-ET	
tk-TM	
tl-PH	
tn-ZA	
to-TO	

Description

Note

A free form note.

Name Note

Base XSD Type: string

Reference

These field(s) use this type: **ReferenceId.**

Reference notation

Name Reference

Base XSD Type: string

ReferenceNumber

Reference number

Name ReferenceNumber

Base XSD Type: string

SecondaryPassword

These field(s) use this type: **SecondaryPassword.**

Secondary password used to validate access to the dealer information

Name SecondaryPassword

Base XSD Type: string

ShortMfg

These field(s) use this type: **SenderNameCode,DestinationNameCode.**

Short Manfacturer or RSP Codes

Name ShortMfg

Base XSD Type: string

SystemVersion

These field(s) use this type: **SystemVersion.**

The sender's software version number.

Name

SystemVersion

Base XSD Type: string

Text

These field(s) use this type:

 $\underline{CreatorNameCode, StoreNumber, AreaNumber, Password, DestinationSoftwareCode, DestinationSoftware, StoreNumber, AreaNumber, LogicalId, Component, Toucher, Component, Compone$

Indicates generic text type

Name

Text

Base XSD Type: string

URI

These field(s) use this type: **SenderURI,DestinationURI.**

URI

Name

URI

Base XSD Type: anyURI

Fields and Global Attributes

Global declarations are items such as elements, attribute groups, and group definitions. These items are not defined within any particular component. A component may reference these definitions. Within a STAR XML Schemas these are typically known as global fields.

ApplicationArea

These field(s) use this type: **ApplicationArea**.

Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.

Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.

Name	ApplicationArea
Туре	ApplicationArea
Nillable	no
Abstract	no

XML Instance Representation

Detail

Name

Type FinancialStatementDetail

Nillable no

Abstract no

XML Instance Representation

<Detail>
 <AccountId> AccountId </AccountId> [1]
 <AccountValue> AccountValue </AccountValue> [1]
</Detail>

FinancialStatement

These field(s) use this type: **FinancialStatement.**

Name
FinancialStatement

Type
FinancialStatement

Nillable
no
Abstract
no

XML Instance Representation

<FinancialStatement>
 <Header> ... </Header> [1]
 <Detail> ... </Detail> [1..*]
</FinancialStatement>

Header

Name Header

Type FinancialStatementHeader

Nillable no

XML Instance Representation

```
<Header>
<DocumentDateTime> DocumentDateTime </DocumentDateTime> [0..1]
<SecondaryPassword> SecondaryPassword </SecondaryPassword> [0..1]
<SecondaryDealerNumber> SecondaryDealerNumber </SecondaryDealerNumber> [0..1]
<AccountingDate> AccountingDate </AccountingDate> [1]
<AccountingTerm> AccountingTerm </AccountingTerm> [0..1]
<Count> Count </Count> [0..1]
<FileVersionNumber> FileVersionNumber </FileVersionNumber> [0..1]
<OrganizationId> OrganizationId </OrganizationId> [0..1]
</Header>
```

Process

These field(s) use this type: **Process.**

The Process verb is used to request processing of the associated noun by the receiving application or business to party. In a typical external exchange scenario a Process BOD is considered to be a legally binding message. For example, if a customer sends a ProcessPurchaseOrder BOD to a supplier and the supplier acknowledgeSurchaseOrder, then the customer is obligated to fullfil the agreement, unless of course other BODs are allowed to cancel or change the original order.

Name	Process
Туре	Process
Nillable	no
Abstract	no

XML Instance Representation

```
<Process
confirm="ConfirmType [0..1]"
acknowledge="AcknowledgementType [0..1]">
    <Criteria> ActionExpressionCriteria </Criteria> [0..1]
</Process>
```

These field(s) use this type: **ProcessFinancialStatement.**

Name	ProcessFinancialStatement
Туре	ProcessFinancialStatement
Nillable	no
Abstract	no

XML Instance Representation

```
<ProcessFinancialStatement
revision="Text [0..1]"
release="8.1-Lite [0..1]"
environment="Text [0..1]"
lang="Language [0..1]"
bodVersion="Text [0..1]">
    <ApplicationArea> ... </ApplicationArea> [1]
    <DataArea> ProcessFinancialStatementDataArea </DataArea> [1]
    </ProcessFinancialStatement>
```

Verb

These field(s) use this type: **Verb.**

Name	Verb
Туре	Verb
Nillable	no
Abstract	yes

XML Instance Representation

<Verb/>