



Standards for Technology in Automotive Retail

**Implementation Guidelines
Confirm BODDRAFT
Repository Version Rev4.4.4**

Table of Contents

Overview	1
Schema Field Usage	1
Business Scenario	1
Relationship Diagram	2
Schema Document Properties	3
Components and Data Types	4
ApplicationArea	4
BOD	5
BODHeader	6
BusinessObjectDocument	7
Confirm	9
ConfirmBOD	9
ConfirmBODDataArea	10
Description	11
Destination	12
DocumentId	13
DocumentReference	14
ErrorMessage	14
GenericDocumentReference	15
HeaderBase	16
Id	16
LocationId	17
Noun	17
NounOutcome	17
OutcomeValue	18
PartyId	19
ProcessingFailure	19
ProcessingOutcomeMessage	20
ProcessingSuccess	20
ReferenceName	21
SecondaryDealerNumber	21
Sender	22

SenderBase	25
ServiceId	26
Signature	26
SuccessMessage	27
Verb	28
WarningMessage	28
.....	
.....	
ApplicationReasonCode	29
Code	29
Country	29
DateTime	41
DocumentDateTime	42
ErrorType	42
Indicator	42
Language	43
MessageReasonCode	50
Note	51
Reference	51
ReferenceNumber	52
ReferenceValue	52
SecondaryPassword	52
ShortMfg	52
SystemVersion	53
Text	53
Type	53
URI	53
Fields and Global Attributes	55
ApplicationArea	55
BOD	55
BODFailure	56
BODOutcomeValue	56

BODPartialSuccess	57
BODSuccess	57
Confirm	58
ConfirmBOD	58
ErrorMessage	59
Header	60
Noun	60
NounFailure	61
NounOutcome	61
NounOutcomeValue	62
NounSuccess	62
SuccessMessage	63
Verb	63
WarningMessage	64

Confirm BOD

Confirm BOD Guidelines

Overview

This document is a guideline on how to use the Confirm BOD Business Object Document (BOD). Confirm BOD has been defined in the context of STAR for the Automotive Retail Industry. The scope of this BOD is to define the Confirm BOD process for individual consumers who service their automobiles through their OEM's authorized Dealers. The focus is on Dealer and OEM interactions, not third party organizations. NOTE: Although this is the traditional use of the Confirm BOD, this BOD could be used to send Confirm BOD information between any two business parties.

Implementation Guidelines provide detailed information regarding the structure and meaning of the Confirm BOD BOD and corresponds directly to the Confirm BOD schema. In addition to structure and meaning, the Implementation Guidelines identify various business rules for specific fields/components that due to their nature, i.e. field interdependence, are not possible to express using schema. Please note that although these business rules are not included in the schema, they **MUST** be followed to be STAR Compliant. Therefore, the Confirm BOD Implementation Guidelines must be used in concert with the Confirm BOD schema during development and should **NOT** be considered a supplement or substitution to the schema. For more information regarding STAR XML Data Compliance, please review the STAR Data Compliance Guidelines document located on the STAR Web site.

For a copy of the corresponding Confirm BOD schema, please download the appropriate STAR schema repository from the XML portion of the STAR website (www.starstandard.org). Prior to downloading the schema, users are encouraged to download the STAR XML Reference/Implementation document also located on the XML portion of the STAR website. This document provides an overview of the STAR BOD development methodology, how to download and read STAR schema, and various frequently asked questions related to the implementation of STAR BODs.

STAR has followed the Open Application Group's Business Object Document methodology to develop the Confirm BOD BOD. Where possible, STAR has mapped to existing OAGI fields and components. Note however that the STAR Confirm BOD BOD is unique to the Retail Automotive industry and is not an extension of any existing OAGIS BODs.

For more information on the Open Applications Group's BODs and related documentation please refer to the Open Applications Group's Web site at (www.openapplications.org).

Schema Field Usage

STAR uses the same Noun in the schema for all the Noun/Verb combinations of the Confirm BOD except the Get verb. Please refer to each Noun/Verb combination within this document to understand the requirements for each specific BOD. Although the Noun will always have every field defined for the Noun in the schema, each Noun/Verb combination may not use all of the fields. If a field is not used by a BOD, it will be noted in the business rules.

Business Scenario

Schema Document Properties

Declared Namespaces

A schema can contain more than one namespace. According to Whatis.com, "In general, a namespace uniquely identifies a set of names so that there is no ambiguity when objects having different origins but the same names are mixed together." An example would be two namespaces that both defined an element called ID, without a namespace it would be impossible to determine which definition was being used.

Prefix	Namespace
Default namespace	http://www.starstandards.org/STAR
xml	http://www.w3.org/XML/1998/namespace
xsd	http://www.w3.org/2001/XMLSchema

Components and Data Types

Global definitions include components, code lists, and data types. Components are used to build the data structures that make up a Noun and it's requirements. Data types specify the type of data that a component's fields may contain. Not all definitions are included in this documentation. Please see either the STAR Code List guideline or Data Type Guidelines for further information.

ApplicationArea

These field(s) use this type: OriginalApplicationArea,ApplicationArea.

Name	ApplicationArea
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
Sender	Identifies characteristics and control identifiers that relate to the application that created the Business Object Document. The sender area can indicate the logical location of the application and/or database server, the application, and the task that was processing to create the BOD.	R	
CreationDateTime	is the date time stamp that the given instance of the Business Object Document was created. This date must not be modified during the life of the Business Object Document.	R	DateTime fields must be formatted as XML Schema Datetimes in UTC/GMT format without offsets. Example: 2003-11-05T13:15:30Z

Confirm BOD

Field / Component	Description	R/O	Business Rule
Signature	If the BOD is to be signed the signature element is included, otherwise it is not. Signature supports any digital signature that maybe used by an implementation of OAGIS. The qualifyingAgency identifies the agency that provided the format for the signature. This element supports any digital signature specification that is available today and in the future. This is accomplished by not actually defining the content but by allowing the implementation to specify the digital signature to be used via an external XML Schema namespace declaration. The Signature element is defined to have any content from any other namespace. This allows the user to carry a digital signature in the xml instance of a BOD. The choice of which digital signature to use is left up to the user and their integration needs.		
BODId	The BODId provides a place to carry a Globally Unique Identifier (GUID) that will make each Business Object Document instance uniquely identifiable. This is a critical success factor to enable software developers to use the Globally Unique Identifier (GUID) to build the following services or capabilities: 1. Legally binding transactions, 2. Transaction logging, 3. Exception handling, 4. Re-sending, 5. Reporting, 6. Confirmations, 7. Security.	O	
Destination	Information related to the receiver of the BOD	R	

XML Instance Representation

```
<...>
  <Sender> Sender </Sender> [1]
  <CreationDateTime> DateTime </CreationDateTime> [1]
  <Signature> Signature </Signature> [0..1]
  <BODId> Code </BODId> [0..1]
  <Destination> Destination </Destination> [1]
</...>
```

BOD

These field(s) use this type: **BOD**.

Name	BOD
------	-----

Confirm BOD

Abstract no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
Noun		R	
Header	Information about the BOD that was processed, including identifying information and a summary-level indication of the outcome of processing the BOD.	R	
NounOutcome	Each NounOutcome captures the outcome of processing each noun of the O BOD.		

XML Instance Representation

```
<...>  
  <Header> ... </Header> [1]  
  <NounOutcome> ... </NounOutcome> [0..*]  
</...>
```

BODHeader

These field(s) use this type: **Header**.

Information about the BOD that was processed, including identifying information and a summary-level indication of the outcome of processing the BOD.

Name BODHeader

Abstract no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
DocumentDateTime	Is the date and time the document was last created. This is not the date and time that the BOD message instance was created.	O	
SecondaryPassword	Secondary password used to validate access to the dealer information	O	

Confirm BOD

Field / Component	Description	R/O	Business Rule
SecondaryDealerNumber	Identifies secondary dealer number if different than primary "Dealer Number"	O	
OriginalApplicationArea	A copy of the ApplicationArea for the original BOD that was processed. Present either as additional reference information, or for use in identifying the BOD in situations where a BODReference is not known.	R	
OriginalBODReference	Reference to the original BOD that was processed.	O	(INACTIVE)
BODOutcomeValue	The possible BOD-level outcomes; an extensible list.	O	

XML Instance Representation

```
<...>
  <DocumentDateTime> DocumentDateTime </DocumentDateTime> [0..1]
  <SecondaryPassword> SecondaryPassword </SecondaryPassword> [0..1]
  <SecondaryDealerNumber> SecondaryDealerNumber </SecondaryDealerNumber> [0..1]
  <OriginalApplicationArea> ApplicationArea </OriginalApplicationArea> [1]
  <OriginalBODReference> GenericDocumentReference </OriginalBODReference> [0..1]
  <BODOutcomeValue> ... </BODOutcomeValue> [0..1]
</...>
```

BusinessObjectDocument

Name	BusinessObjectDocument
Abstract	no

Attributes

Field / Component	Description	R/O	Business Rule
revision	This should contain the STAR repository version in the following recommended format. 4.2.1_M20080416. Where the first part indicates the version of the STAR repository and anything after the _ indicates the Milestone build that is being used. If referring to an official published version then only the STAR Repository version is required.	O	

Confirm BOD

Field / Component	Description	R/O	Business Rule
release	Indicates the OAGIS release that this BOD belongs.	O	
environment	Indicates whether this BOD is being sent in a "Test" or a "Production" mode. If the BOD is being sent in a test mode, it's information should not affect the business operation. However, if the BOD is sent in "Production" mode it is assumed that all test has been complete and the contents of the BOD are to affect the operation of the receiving business application(s).	O	
lang	Indicates the language that the contents of the BOD is in unless otherwise stated.	O	
bodVersion	Deprecated as of STAR 4.2.2. It is recommended to use the revision attribute to identify the repository and the noun. May be removed in a new major version of the STAR repository. Indicates the version number of the BOD.	O	

Data Elements and Components

Field / Component	Description	R/O	Business Rule
ApplicationArea	Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of. Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.	R	

XML Instance Representation

```
<...  
revision="Text [0..1]"  
release="8.1-Lite [0..1]"  
environment="Text [0..1]"
```

Confirm BOD

```
lang="Language [0..1]"
bodVersion="Text [0..1]">
  <ApplicationArea> ... </ApplicationArea> [1]
</...>
```

Confirm

These field(s) use this type: Confirm.

Name	Confirm
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
Verb		R	

XML Instance Representation

```
<.../>
```

ConfirmBOD

These field(s) use this type: ConfirmBOD.

Name	ConfirmBOD
Abstract	no

Data Elements and Components

Confirm BOD

Field / Component	Description	R/O	Business Rule
ApplicationArea	Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of. Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.	R	
DataArea		R	

XML Instance Representation

```
<...  
revision="Text [0..1]"  
release="8.1-Lite [0..1]"  
environment="Text [0..1]"  
lang="Language [0..1]"  
bodVersion="Text [0..1]">  
  <ApplicationArea> ... </ApplicationArea> [1]  
  <DataArea> ConfirmBODDataArea </DataArea> [1]  
</...>
```

ConfirmBODDataArea

These field(s) use this type: **DataArea**.

Name	ConfirmBODDataArea
Abstract	no

Data Elements and Components

Confirm BOD

Field / Component	Description	R/O	Business Rule
Confirm	The Confirm verb is used to respond to a request to confirm the receipt of information by the receiving system. The request for confirmation is set by the sending application in the ApplicationArea\Sender\Confirmation field of the original BOD. The Confirm conveys the result of the original request i.e. whether or not the message was understood and was successfully processed. An example of this is Confirm BOD.	R	
BOD	The outcome of processing a specific BOD. Describes overall/summary outcome, plus the outcome of processing each noun of the BOD. Includes noun-specific error and/or warning messages encountered during processing. May include summary and/or roll-up messages at the BOD level.	R	

XML Instance Representation

```
<...>  
  <Confirm> ... </Confirm> [1]  
  <BOD> ... </BOD> [1..*]  
</...>
```

Description

These field(s) use this type: **Description,Description.**

Description

Name	Description
Abstract	no

Attributes

Field / Component	Description	R/O	Business Rule
language	The ISO language code that the description is written.	O	

XML Instance Representation

Confirm BOD

```
<...  
language="Language [0..1]">  
  xsd:string  
</...>
```

Destination

These field(s) use this type: **Destination**.

Name	Destination
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
DestinationNameCode	Code for destination of file (i.e.Short Manufacturer or DSP code)	O	Must use a valid code from the ShortMfg/RSP list on http://www.starstandards.org
DestinationURI	Physical address of the destination	O	
DestinationSoftwareCode	Additional information about the destination application	O	
DestinationSoftware	For which software destination file is intended (may not be known).	O	
DealerNumber	Target Dealer Code receiving information	O	
StoreNumber	Dealer code store number (DMS assigned)	O	
AreaNumber	Dealer code area number (DMS vendor assigned)	O	
DealerCountry	Target Dealer country location	O	
PartyId	The Party Id field uniquely identifies the Receiver of the message. This element can be used for parties within the Automotive Community as well as external parties. Party Id is not intended as a replacement for the Dealer Number. Suggested formats for OEMs or other large institutions include: DUNs Number, ShortMfgCode + DUNs, or ShortMfgCode. The suggested format for Dealers is: ShortMfgCode+Dealer Number.	O	

Confirm BOD

Field / Component	Description	R/O	Business Rule
LocationId	The Location Id field uniquely identifies the location of the Receiver of a O message. This Id may be aligned with a physical address or data centers. This field provides an additional level of granularity beyond the usage of the Party Id for additional routing and deliver of data.		
ServiceId	The Service Id field identifies the particular service to which a message is being sent, e.g., an inventory service.	O	

XML Instance Representation

```
<...>
  <DestinationNameCode> ShortMfg </DestinationNameCode> [0..1]
  <DestinationURI> URI </DestinationURI> [0..1]
  <DestinationSoftwareCode> Text </DestinationSoftwareCode> [0..1]
  <DestinationSoftware> Text </DestinationSoftware> [0..1]
  <DealerNumber> PartyId </DealerNumber> [0..1]
  <StoreNumber> Text </StoreNumber> [0..1]
  <AreaNumber> Text </AreaNumber> [0..1]
  <DealerCountry> Country </DealerCountry> [0..1]
  <PartyId> PartyId </PartyId> [0..1]
  <LocationId> LocationId </LocationId> [0..1]
  <ServiceId> ServiceId </ServiceId> [0..1]
</...>
```

DocumentId

These field(s) use this type: **DocumentId,DocumentId.**

Is the identifier for the document.

Name	DocumentId
Abstract	no

XML Instance Representation

```
<...>
  Id
```

Confirm BOD

</...>

DocumentReference

Identifies another document within the scope of the OAGIS specification, such as a PurchaseOrder or Invoice that maybe associated with a particular Business Object Document.

Name	DocumentReference
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
-------------------	-------------	-----	---------------

XML Instance Representation

<.../>

ErrorMessage

These field(s) use this type: ErrorMessage.

Name	ErrorMessage
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
ProcessingOutcomeMessage		R	
ErrorType		O	
ReferenceName		O	
ReferenceValue		O	

XML Instance Representation

Confirm BOD

```
<...>
Start Choice [1]
  <ApplicationReasonCode> ApplicationReasonCode </ApplicationReasonCode> [1]
  <Description> Description </Description> [1..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [1]
  <Description> Description </Description> [0..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [0..1]
End Choice
  <ErrorType> ErrorType </ErrorType> [0..1]
  <ReferenceName> ReferenceName </ReferenceName> [0..1]
  <ReferenceValue> ReferenceValue </ReferenceValue> [0..1]
</...>
```

GenericDocumentReference

These field(s) use this type: OriginalBODReference.

Name	GenericDocumentReference
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
DocumentReference	Identifies another document within the scope of the OAGIS specification, such as a PurchaseOrder or Invoice that maybe associated with a particular Business Object Document.	R	
DocumentId		O	
DocumentDateTime	The Datetime of the referenced document.	O	

XML Instance Representation

```
<...>
  <DocumentId> DocumentId </DocumentId> [0..1]
  <DocumentDateTime> DocumentDateTime </DocumentDateTime> [0..1]
</...>
```

Confirm BOD

HeaderBase

Used on all STAR BODs

Name	HeaderBase
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
DocumentDateTime	Is the date and time the document was last created. This is not the date and time that the BOD message instance was created.	O	
SecondaryPassword	Secondary password used to validate access to the dealer information	O	
SecondaryDealerNumber	Identifies secondary dealer number if different than primary "Dealer Number"	O	

XML Instance Representation

```
<...>
  <DocumentDateTime> DocumentDateTime </DocumentDateTime> [0..1]
  <SecondaryPassword> SecondaryPassword </SecondaryPassword> [0..1]
  <SecondaryDealerNumber> SecondaryDealerNumber </SecondaryDealerNumber> [0..1]
</...>
```

Id

These field(s) use this type: **AuthorizationId**.

Party Identification number

Name	Id
Abstract	no

XML Instance Representation

Confirm BOD

```
<...>
  xsd:string
</...>
```

LocationId

These field(s) use this type: LocationId,LocationId.

Code identifying a physical location

Name	LocationId
Abstract	no

XML Instance Representation

```
<...>
  Id
</...>
```

Noun

These field(s) use this type: Noun.

Name	Noun
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
-------------------	-------------	-----	---------------

XML Instance Representation

```
<.../>
```

NounOutcome

These field(s) use this type: NounOutcome.

Confirm BOD

Each NounOutcome captures the outcome of processing each noun of the BOD.

Name	NounOutcome
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
DocumentId		O	
NounOutcomeValue	The specific outcome of processing the noun, with supporting detail.	O	
DocumentDateTime	The date and time the document was last created. This is not the date and O time that the BOD message instance was created.		

XML Instance Representation

```
<...>
  <DocumentId> DocumentId </DocumentId> [0..1]
  <NounOutcomeValue> ... </NounOutcomeValue> [0..1]
  <DocumentDateTime> DocumentDateTime </DocumentDateTime> [0..1]
</...>
```

OutcomeValue

These field(s) use this type: **BODOutcomeValue,NounOutcomeValue.**

Name	OutcomeValue
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
-------------------	-------------	-----	---------------

XML Instance Representation

```
<.../>
```


Confirm BOD

PartyId

These field(s) use this type: DealerNumber,PartyId,DealerNumber,PartyId.

Party Identification Number

Name	PartyId
Abstract	no

XML Instance Representation

```
<...>  
  Id  
</...>
```

ProcessingFailure

These field(s) use this type: BODPartialSuccess,BODFailure,NounFailure.

Name	ProcessingFailure
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
OutcomeValue		R	
ErrorMessage	Error message encountered during processing.	O	
WarningMessage	Non-fatal warning message encountered during processing.	O	

XML Instance Representation

```
<...>  
  <ErrorMessage> ... </ErrorMessage> [0..*]  
  <WarningMessage> ... </WarningMessage> [0..*]  
</...>
```

Confirm BOD

ProcessingOutcomeMessage

Name	ProcessingOutcomeMessage
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
ApplicationReasonCode		R	
Description		R	
MessageReasonCode		R	
Description		O	
MessageReasonCode		O	

XML Instance Representation

```
<...>
Start Choice [1]
  <ApplicationReasonCode> ApplicationReasonCode </ApplicationReasonCode> [1]
  <Description> Description </Description> [1..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [1]
  <Description> Description </Description> [0..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [0..1]
End Choice
</...>
```

ProcessingSuccess

These field(s) use this type: **BODSuccess,NounSuccess.**

Name	ProcessingSuccess
------	-------------------

Confirm BOD

Abstract no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
OutcomeValue		R	
WarningMessage	Non-fatal warning message encountered during processing.	O	
SuccessMessage	Message indicating a success.	O	

XML Instance Representation

```
<...>
  <WarningMessage> ... </WarningMessage> [0..*]
  <SuccessMessage> ... </SuccessMessage> [0..*]
</...>
```

ReferenceName

These field(s) use this type: **ReferenceName**.

The name of the field/tag that references/identifies the key data elements the senders request/response bod.

Name ReferenceName

Abstract no

XML Instance Representation

```
<...
language="Language [0..1]">
  Description
</...>
```

SecondaryDealerNumber

These field(s) use this type: **SecondaryDealerNumber**.

Confirm BOD

Identifies secondary dealer number if different than primary "Dealer Number"

Name	SecondaryDealerNumber
Abstract	no

XML Instance Representation

```
<...>  
  Id  
</...>
```

Sender

These field(s) use this type: Sender.

Name	Sender
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
LogicalId	Provides the logical location of the server and applications from which the Business Object Document originated. It can be used to establish a logical to physical mapping, however its use is optional. Each system or combination of systems should maintain an external central reference table containing the logical names or logical addresses of the application systems in the integration configuration. This enables the logical names to be mapped to the physical network addresses of the resources needed on the network. Note: The technical implementation of this Domain Naming Service is not dictated by this specification. This logical to physical mapping may be done at execution time by the application itself or by a middleware transport mechanism, depending on the integration architecture used. This provides for a simple but effective directory access capability while maintaining application independence from the physical location of those resources on the network	O	

Confirm BOD

Field / Component	Description	R/O	Business Rule
Component	Provides a finer level of control than Logical Identifier and represents the business application that issued the Business Object Document. Its use is optional. For STAR's use this is the DCS Software code name		
Task	Describes the business event that initiated the need for the Business Object Document to be created. For STAR, the task is defined in the Implementation Guidelines for each BOD. It is usually a short description of the BOD. Ex: SalesLead, CreditDecision, etc.	R	
ReferenceId	Enables the sending application to indicate the instance identifier of the event or task that caused the BOD to be created. This is used to correlate a response BOD to an originating BOD	O	
AuthorizationId	Identifies the authorization level of the user or application that is sending the Business Object Document Message. This authorization level being recognized by the receiving system indicates what can be done on the receiving system. For STAR, this is the User ID.	O	
CreatorNameCode	DCS Software Creator Code	R	
SenderNameCode	Additional information about the sending platform (i.e., Short MFG or DSP code).	R	Must use a valid code from the ShortMfg/RSP list on http://www.starstandards.org
SenderURI	Physical address of the sender	O	
DealerNumber	Dealer Code of source of information	O	
StoreNumber	Dealer code store number (DMS assigned)	O	
AreaNumber	Dealer code area number (DMS vendor assigned)	O	
DealerCountry	Source Dealer country location	O	
Language	This code is used to define the language of the data used in this transaction	O	
DeliverPendingMailInd	Indicates if the user requests to receive pending mail that has been stored and has yet not been delivered yet. By selecting 0, the user will only receive the response for the current transaction the user is performing.	O	

Confirm BOD

Field / Component	Description	R/O	Business Rule
Password	Token for application specific authentication. Used to authenticate dealership/users through application specific security	O	
SystemVersion	The sender's software version number.	O	
PartyId	The Party Id field uniquely identifies the Sender of the message. This element can be used for parties within the Automotive Community as well as external parties. Party Id is not intended as a replacement for the Dealer Number. Suggested formats for OEMs or other large institutions include: DUNs Number, ShortMfgCode + DUNs, or ShortMfgCode. The suggested format for Dealers is: ShortMfgCode+Dealer Number.	O	
LocationId	The Location Id field uniquely identifies the location of the Sender of a message. This Id may be aligned with a physical address or data centers. This field provides an additional level of granularity beyond the usage of the Party Id for additional routing and deliver of data.	O	
ServiceId	The Service Id field identifies the particular service from which a message is being sent, e.g., an inventory service.	O	

XML Instance Representation

```

<...>
  <LogicalId> Text </LogicalId> [0..1]
  <Component> Text </Component> [1]
  <Task> Text </Task> [1]
  <ReferenceId> Reference </ReferenceId> [0..1]
  <AuthorizationId> Id </AuthorizationId> [0..1]
  <CreatorNameCode> Text </CreatorNameCode> [1]
  <SenderNameCode> ShortMfg </SenderNameCode> [1]
  <SenderURI> URI </SenderURI> [0..1]
  <DealerNumber> PartyId </DealerNumber> [0..1]
  <StoreNumber> Text </StoreNumber> [0..1]
  <AreaNumber> Text </AreaNumber> [0..1]
  <DealerCountry> Country </DealerCountry> [0..1]
  <Language> Language </Language> [0..1]
  <DeliverPendingMailInd> Indicator </DeliverPendingMailInd> [0..1]
  <Password> Text </Password> [0..1]

```

Confirm BOD

```
<SystemVersion> SystemVersion </SystemVersion> [0..1]
<PartyId> PartyId </PartyId> [0..1]
<LocationId> LocationId </LocationId> [0..1]
<ServiceId> ServiceId </ServiceId> [0..1]
</...>
```

SenderBase

Name	SenderBase
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
LogicalId	Provides the logical location of the server and applications from which the Business Object Document originated. It can be used to establish a logical to physical mapping, however its use is optional. Each system or combination of systems should maintain an external central reference table containing the logical names or logical addresses of the application systems in the integration configuration. This enables the logical names to be mapped to the physical network addresses of the resources needed on the network. Note: The technical implementation of this Domain Naming Service is not dictated by this specification. This logical to physical mapping may be done at execution time by the application itself or by a middleware transport mechanism, depending on the integration architecture used. This provides for a simple but effective directory access capability while maintaining application independence from the physical location of those resources on the network	O	
Component	Provides a finer level of control than Logical Identifier and represents the business application that issued the Business Object Document. Its use is optional. For STAR's use this is the DCS Software code name		
Task	Describes the business event that initiated the need for the Business Object Document to be created. For STAR, the task is defined in the Implementation Guidelines for each BOD. It is usually a short description of the BOD. Ex: SalesLead, CreditDecision, etc.	R	

Confirm BOD

Field / Component	Description	R/O	Business Rule
ReferenceId	Enables the sending application to indicate the instance identifier of the event or task that caused the BOD to be created. This is used to correlate a response BOD to an originating BOD	O	
AuthorizationId	Identifies the authorization level of the user or application that is sending the Business Object Document Message. This authorization level being recognized by the receiving system indicates what can be done on the receiving system. For STAR, this is the User ID.	O	

XML Instance Representation

```
<...>
  <LogicalId> Text </LogicalId> [0..1]
  <Component> Text </Component> [1]
  <Task> Text </Task> [1]
  <ReferenceId> Reference </ReferenceId> [0..1]
  <AuthorizationId> Id </AuthorizationId> [0..1]
</...>
```

ServiceId

These field(s) use this type: **ServiceId,ServiceId.**

The Service Id field identifies the particular service to or from which a message is being sent, e.g., an inventory service.

Name	ServiceId
Abstract	no

XML Instance Representation

```
<...>
  Id
</...>
```

Signature

These field(s) use this type: **Signature.**

Confirm BOD

Name	Signature
Abstract	no

Attributes

Field / Component	Description	R/O	Business Rule
qualifyingAgency		O	

Data Elements and Components

Field / Component	Description	R/O	Business Rule
-------------------	-------------	-----	---------------

XML Instance Representation

```
<...  
qualifyingAgency="Text [0..1]">  
Allow any elements from any namespace (strict validation). [0..1]  
</...>
```

SuccessMessage

These field(s) use this type: SuccessMessage.

Name	SuccessMessage
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
ProcessingOutcomeMessage		R	

XML Instance Representation

```
<...>  
Start Choice [1]
```

Confirm BOD

```
<ApplicationReasonCode> ApplicationReasonCode </ApplicationReasonCode> [1]
<Description> Description </Description> [1..*]
<MessageReasonCode> MessageReasonCode </MessageReasonCode> [1]
<Description> Description </Description> [0..*]
<MessageReasonCode> MessageReasonCode </MessageReasonCode> [0..1]
End Choice
</...>
```

Verb

These field(s) use this type: Verb.

Name	Verb
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
-------------------	-------------	-----	---------------

XML Instance Representation

```
<.../>
```

WarningMessage

These field(s) use this type: WarningMessage.

Name	WarningMessage
Abstract	no

Data Elements and Components

Field / Component	Description	R/O	Business Rule
ProcessingOutcomeMessage		R	

Confirm BOD

XML Instance Representation

```
<...>
Start Choice [1]
  <ApplicationReasonCode> ApplicationReasonCode </ApplicationReasonCode> [1]
  <Description> Description </Description> [1..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [1]
  <Description> Description </Description> [0..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [0..1]
End Choice
</...>
```

ApplicationReasonCode

These field(s) use this type: **ApplicationReasonCode**.

A software application specific reason code. Used for indicating numeric or text encoded error, success, and warning messages.

Name	ApplicationReasonCode
------	-----------------------

*Base XSD Type: string

Code

These field(s) use this type: **BODId**.

Unique code name

Name	Code
------	------

*Base XSD Type: string

Country

These field(s) use this type: **DealerCountry,DealerCountry**.

Country in which the Address is in. Conforms to ISO 3166-2. AF -AFGHANISTAN AL -ALBANIA DZ -ALGERIA AS -AMERICAN SAMOA AD -ANDORRA AO -ANGOLA AI -ANGUILLA AQ -ANTARCTICA AG -ANTIGUA AND BARBUDA AR -ARGENTINA AM -ARMENIA AW -ARUBA AU -AUSTRALIA AT -AUSTRIA AZ -AZERBAIJAN BS -BAHAMAS BH -BAHRAIN BD -BANGLADESH BB -BARBADOS BY

Confirm BOD

-BELARUS BE -BELGIUM BZ -BELIZE BJ -BENIN BM -BERMUDA BT -BHUTAN BO -BOLIVIA BA -BOSNIA AND HERZEGOVINA BW
 -BOTSWANA BV -BOUVET ISLAND BR -BRAZIL IO -BRITISH INDIAN OCEAN TERRITORY BN -BRUNEI DARUSSALAM BG -BULGARIA
 BF -BURKINA FASO BI -BURUNDI KH -CAMBODIA CM -CAMEROON CA -CANADA CV -CAPE VERDE KY -CAYMAN ISLANDS CF
 -CENTRAL AFRICAN REPUBLIC TD -CHAD CL -CHILE CN -CHINA CX -CHRISTMAS ISLAND CC -COCOS (KEELING) ISLANDS CO
 -COLOMBIA KM -COMOROS CG -CONGO CD -CONGO, THE DEMOCRATIC REPUBLIC OF THE CK -COOK ISLANDS CR -COSTA RICA CI
 -CÔTE D'IVOIRE HR -CROATIA CU -CUBA CY -CYPRUS CZ -CZECH REPUBLIC DK -DENMARK DJ -DJIBOUTI DM -DOMINICA DO
 -DOMINICAN REPUBLIC EC -ECUADOR EG -EGYPT SV -EL SALVADOR GQ -EQUATORIAL GUINEA ER -ERITREA EE -ESTONIA ET
 -ETHIOPIA FK -FALKLAND ISLANDS (MALVINAS) FO -FAROE ISLANDS FJ -FIJI FI -FINLAND FR -FRANCE GF -FRENCH GUIANA PF
 -FRENCH POLYNESIA TF -FRENCH SOUTHERN TERRITORIES GA -GABON GM -GAMBIA GE -GEORGIA DE -GERMANY GH -GHANA GI
 -GIBRALTAR GR -GREECE GL -GREENLAND GD -GRENADA GP -GUADELOUPE GU -GUAM GT -GUATEMALA GN -GUINEA GW
 -GUINEA-BISSAU GY -GUYANA HT -HAITI HM -HEARD ISLAND AND MCDONALD ISLANDS VA -HOLY SEE (VATICAN CITY STATE)
 HN -HONDURAS HK -HONG KONG HU -HUNGARY IS -ICELAND IN -INDIA ID -INDONESIA IR -IRAN, ISLAMIC REPUBLIC OF IQ -IRAQ
 IE -IRELAND IL -ISRAEL IT -ITALY JM -JAMAICA JP -JAPAN JO -JORDAN KZ -KAZAKHSTAN KE -KENYA KI -KIRIBATI KP -KOREA,
 DEMOCRATIC PEOPLE'S REPUBLIC OF KR -KOREA, REPUBLIC OF KW -KUWAIT KG -KYRGYZSTAN LA -LAO PEOPLE'S DEMOCRATIC
 REPUBLIC LV -LATVIA LB -LEBANON LS -LESOTHO LR -LIBERIA LY -LIBYAN ARAB JAMAHIRIYA LI -LIECHTENSTEIN LT
 -LITHUANIA LU -LUXEMBOURG MO -MACAO MK -MACEDONIA, THE FORMER YUGOSLAV REPUBLIC OF MG -MADAGASCAR MW
 -MALAWI MY -MALAYSIA MV -MALDIVES ML -MALI MT -MALTA MH -MARSHALL ISLANDS MQ -MARTINIQUE MR -MAURITANIA
 MU -MAURITIUS YT -MAYOTTE MX -MEXICO FM -MICRONESIA, FEDERATED STATES OF MD -MOLDOVA, REPUBLIC OF MC
 -MONACO MN -MONGOLIA MS -MONTSERRAT MA -MOROCCO MZ -MOZAMBIQUE MM -MYANMAR NA -NAMIBIA NR -NAURU NP
 -NEPAL NL -NETHERLANDS AN -NETHERLANDS ANTILLES NC -NEW CALEDONIA NZ -NEW ZEALAND NI -NICARAGUA NE -NIGER
 NG -NIGERIA NU -NIUE NF -NORFOLK ISLAND MP -NORTHERN MARIANA ISLANDS NO -NORWAY OM -OMAN PK -PAKISTAN PW
 -PALAU PS -PALESTINIAN TERRITORY, OCCUPIED PA -PANAMA PG -PAPUA NEW GUINEA PY -PARAGUAY PE -PERU PH -PHILIPPINES
 PN -PITCAIRN PL -POLAND PT -PORTUGAL PR -PUERTO RICO QA -QATAR RE -RÅÅ#UNION RO -ROMANIA RU -RUSSIAN
 FEDERATION RW -RWANDA SH -SAINT HELENA KN -SAINT KITTS AND NEVIS LC -SAINT LUCIA PM -SAINT PIERRE AND MIQUELON
 VC -SAINT VINCENT AND THE GRENADINES WS -SAMOA SM -SAN MARINO ST -SAO TOME AND PRINCIPE SA -SAUDI ARABIA SN
 -SENEGAL CS -SERBIA AND MONTENEGRO SC -SEYCHELLES SL -SIERRA LEONE SG -SINGAPORE SK -SLOVAKIA SI -SLOVENIA SB
 -SOLOMON ISLANDS SO -SOMALIA ZA -SOUTH AFRICA GS -SOUTH GEORGIA AND THE SOUTH SANDWICH ISLANDS ES -SPAIN LK
 -SRI LANKA SD -SUDAN SR -SURINAME SJ -SVALBARD AND JAN MAYEN SZ -SWAZILAND SE -SWEDEN CH -SWITZERLAND SY
 -SYRIAN ARAB REPUBLIC TW -TAIWAN, PROVINCE OF CHINA TJ -TAJIKISTAN TZ -TANZANIA, UNITED REPUBLIC OF TH -THAILAND
 TL -TIMOR-LESTE TG -TOGO TK -TOKELAU TO -TONGA TT -TRINIDAD AND TOBAGO TN -TUNISIA TR -TURKEY TM
 -TURKMENISTAN TC -TURKS AND CAICOS ISLANDS TV -TUVALU UG -UGANDA UA -UKRAINE AE -UNITED ARAB EMIRATES GB
 -UNITED KINGDOM US -UNITED STATES UM -UNITED STATES MINOR OUTLYING ISLANDS UY -URUGUAY UZ -UZBEKISTAN VU
 -VANUATU VE -VENEZUELA VN -VIET NAM VG -VIRGIN ISLANDS, BRITISH VI -VIRGIN ISLANDS, U.S. WF -WALLIS AND FUTUNA EH
 -WESTERN SAHARA YE -YEMEN ZM -ZAMBIA ZW -ZIMBABWE

Name	Country
------	---------

Confirm BOD

*Base XSD Type: string

Code Value	Description
US	
AF	
AL	
DZ	
AS	
AD	
AO	
AI	
AQ	
AG	
AR	
AM	
AW	
AU	
AT	
AZ	
BS	
BH	
BD	
BB	
BY	

Confirm BOD

Code Value	Description
BE	
BZ	
BJ	
BM	
BT	
BO	
BA	
BW	
BV	
BR	
IO	
BN	
BG	
BF	
BI	
KH	
CM	
CA	
CV	
KY	
CF	
TD	

Confirm BOD

Code Value	Description
CL	
CN	
CX	
CC	
CO	
KM	
CG	
CD	
CK	
CR	
CI	
HR	
CU	
CY	
CZ	
DK	
DJ	
DM	
DO	
EC	
EG	
SV	

Confirm BOD

Code Value	Description
GQ	
ER	
EE	
ET	
FK	
FO	
FJ	
FI	
FR	
GF	
PF	
TF	
GA	
GM	
GE	
DE	
GH	
GI	
GR	
GL	
GD	
GP	

Confirm BOD

Code Value	Description
GU	
GT	
GN	
GW	
GY	
HT	
HM	
VA	
HN	
HK	
HU	
IS	
IN	
ID	
IR	
IQ	
IE	
IL	
IT	
JM	
JP	
JO	

Confirm BOD

Code Value	Description
KZ	
KE	
KI	
KP	
KR	
KW	
KG	
LA	
LV	
LB	
LS	
LR	
LY	
LI	
LT	
LU	
MO	
MK	
MG	
MW	
MY	
MV	

Confirm BOD

Code Value	Description
ML	
MT	
MH	
MQ	
MR	
MU	
YT	
MX	
FM	
MD	
MC	
MN	
MS	
MA	
MZ	
MM	
NA	
NR	
NP	
NL	
AN	
NC	

Confirm BOD

Code Value	Description
NZ	
NI	
NE	
NG	
NU	
NF	
MP	
NO	
OM	
PK	
PW	
PS	
PA	
PG	
PY	
PE	
PH	
PN	
PL	
PT	
PR	
QA	

Confirm BOD

Code Value	Description
RE	
RO	
RU	
RW	
SH	
KN	
LC	
PM	
VC	
WS	
SM	
ST	
SA	
SN	
CS	
SC	
SL	
SG	
SK	
SI	
SB	
SO	

Confirm BOD

Code Value	Description
ZA	
GS	
ES	
LK	
SD	
SR	
SJ	
SZ	
SE	
CH	
SY	
TW	
TJ	
TZ	
TH	
TL	
TG	
TK	
TO	
TT	
TN	
TR	

Confirm BOD

Code Value	Description
TM	
TC	
TV	
UG	
UA	
AE	
GB	
UM	
UY	
UZ	
VU	
VE	
VN	
VG	
VI	
WF	
EH	
YE	
ZM	
ZW	

DateTime

Confirm BOD

These field(s) use this type: **CreationDateTime**.

Date and time conforms to ISO 8601 format rules without offset EX:2003-11-05T13:15:30Z

Name	DateTime
------	----------

*Base XSD Type: dateTime

DocumentDateTime

These field(s) use this type: **DocumentDateTime,DocumentDateTime,DocumentDateTime**.

Is the date and time the document was last created. This is not the date and time that the BOD message instance was created.

Name	DocumentDateTime
------	------------------

*Base XSD Type: dateTime

ErrorType

These field(s) use this type: **ErrorType**.

Defines the type of error that occurred.

Name	ErrorType
------	-----------

*Base XSD Type: string

Indicator

These field(s) use this type: **DeliverPendingMailInd**.

0 = No, 1 = Yes

Name	Indicator
------	-----------

*Base XSD Type: string

Confirm BOD

Code Value	Description
0	
1	

Language

These field(s) use this type: **Language**.

Language conforms to ISO 639-2 rules. Note the format for this field is language-Country (see Country data type for the list of countries with definitions). AA "Afar", AB "Abkhazian", AF "Afrikaans", AM "Amharic", AR "Arabic", AS "Assamese", AY "Aymara", AZ "Azerbaijani", BA "Bashkir", BE "Byelorussian", BG "Bulgarian", BH "Bihari", BI "Bislama", BN "Bengali", BO "Tibetan", BR "Breton", CA "Catalan", CO "Corsican", CS "Czech", CY "Welsh", DA "Danish", DE "German", DZ "Bhutani", EL "Greek", EN "English", ES "Spanish", ET "Estonian", EU "Basque", FA "Persian", FI "Finnish", FJ "Fiji", FO "Faeroese", FR "French", FY "Frisian", GA "Irish", GD "Gaelic", GL "Galician", GN "Guarani", GU "Gujarati", HA "Hausa", HI "Hindi", HR "Croatian", HU "Hungarian", HY "Armenian", IK "Inupiak", IN "Indonesian", IS "Icelandic", IT "Italian", IW "Hebrew", JA "Japanese", JI "Yiddish", JW "Javanese", KA "Georgian", KK "Kazakh", KL "Greenlandic", KM "Cambodian", KN "Kannada", KO "Korean", KS "Kashmiri", KU "Kurdish", KY "Kirghiz", LA "Latin", LN "Lingala", LO "Laothian", LT "Lithuanian", LV "Latvian", MG "Malagasy", MI "Maori", MK "Macedonian", ML "Malayalam", MN "Mongolian", MO "Moldavian", MR "Marathi", MS "Malay", MT "Maltese", MY "Burmese", NA "Nauru", NE "Nepali", NL "Dutch", NO "Norwegian", OC "Occitan", OM "Oromo", OR "Oriya", PA "Punjabi", PL "Polish", PS "Pashto", PT "Portuguese", QU "Quechua", RM "Rhaeto-Romance", RN "Kirundi", RO "Romanian", RU "Russian", RW "Kinyarwanda", SA "Sanskrit", SD "Sindhi", SG "Sangro", SH "Serbo-Croatian", SI "Singhalese", SK "Slovak", SL "Slovenian", SM "Samoan", SN "Shona", SO "Somali", SQ "Albanian", SR "Serbian", SS "Siswati", ST "Sesotho", SU "Sudanese", SV "Swedish", SW "Swahili", TA "Tamil", TE "Tegulu", TG "Tajik", TH "Thai", TI "Tigrinya", TK "Turkmen", TL "Tagalog", TN "Setswana", TO "Tonga", TR "Turkish", TS "Tsonga", TT "Tatar", TW "Twi", UK "Ukrainian", UR "Urdu", UZ "Uzbek", VI "Vietnamese", WO "Wolof", XH "Xhosa", YO "Yoruba", ZH "Chinese", ZU "Zulu"

Name	Language
*Base XSD Type: string	
Code Value	Description
en-US	
en-CA	
aa-ET	
ab-GE	

Confirm BOD

Code Value	Description
af-ZA	
am- ET	
ar-SA	
as-IN	
ay-BO	
az-AZ	
ba-RU	
be-BY	
bg-BG	
bh-IN	
bi-VU	
bn-BD	
bo-BT	
br-FR	
ca-ES	
co-FR	
cs-CZ	
cy-GB	
da-DE	
de-DE	
dz-BT	
el-GR	

Confirm BOD

Code Value	Description
es-ES	
et-EE	
eu-ES	
fa-AF	
fi-FI	
fj-FJ	
fo-FO	
fr-CA	
fr-FR	
fy-NL	
ga-IE	
gd-GB	
gl-ES	
gn-PY	
gu-IN	
ha-NG	
hi-IN	
hr-HR	
hu-HU	
hy-AM	
ik-GL	
in-ID	

Confirm BOD

Code Value	Description
is-IS	
it-IT	
iw-IL	
ja-JP	
ji-IL	
jw-ID	
ka-GE	
kk-KZ	
kl-GL	
km-KH	
kn-IN	
ko-KP	
ko-KR	
ks-IN	
ku-IQ	
ky-CN	
la-VA	
ln-CD	
lo-LA	
lt-LT	
lv-LV	
mg-MG	

Confirm BOD

Code Value	Description
mi-NZ	
mk-MK	
ml-IN	
mn-MN	
mo-MO	
mr-IN	
ms-MY	
mt-MH	
my-MM	
na-NR	
ne-NP	
nl-NL	
no-NO	
oc-FR	
om- ET	
or-IN	
pa-IN	
pl-PL	
ps-PK	
pt-PT	
qu-PE	
rm-CH	

Confirm BOD

Code Value	Description
rn-BI	
ro-RO	
ru-RU	
rw-RW	
sa-IN	
sd-PK	
sg-CF	
sh-HR	
si-LK	
sk-SK	
sl-SI	
sm-WS	
sn-ZW	
so-SO	
sq-AL	
sr-CS	
ss-ZA	
st-ZA	
su-SD	
sv-SE	
sw-TL	
ta-IN	

Confirm BOD

Code Value	Description
te-IN	
tg-TJ	
th-TH	
ti-ET	
tk-TM	
tl-PH	
tn-ZA	
to-TO	
tr-TR	
ts-ZA	
tt-RU	
tw-GH	
uk-UA	
ur-PK	
uz-UZ	
vi-VN	
wo-SN	
xh-ZA	
yo-NG	
zh-CN	
zu-ZA	

Confirm BOD

MessageReasonCode

These field(s) use this type: MessageReasonCode,MessageReasonCode.

Code indicating reason for message.

Name	MessageReasonCode
*Base XSD Type: string	
Code Value	Description
Success	The operation completed successfully. This does not necessarily mean that the BOD was processed. Instead it means that the client's role is done and that it won't receive any error messages later. Type of Response Code: Success.
Accepted	The BOD was received, validated, and accepted. However, it may not have yet been processed. The client should expect to receive a response once process is complete. If no response will be generated, use the "Success" code instead. This is typically used for batch processing. Type of Response Code: Success.
Received	The BOD was received. However, it has not yet been validated or processed yet. The client may receive a response or a ConfirmBOD at a later time. Type of Response Code: Success.
Other	Other
Duplicate Document	This code refers to a document that already exists. This may happen for a BOD such as ProcessPartsOrder where the document identifiers to another existing parts order from the same dealer. Type of Response Code: Error, Warning.
Invalid Required Value	One or more required data elements have invalid values. Type of Response Code: Error.
Invalid Optional Value	One or more optional data elements have invalid values. Type of Response Code: Warning.
Already Performed	This code refers to an operation that has already been performed on a document. This may happen for a BOD such as CancelPartsOrder where the document identifier refer to a parts order that has already been cancelled. Type of Response Code: Error.

Confirm BOD

Code Value	Description
Cannot Perform	This code refers to an operation that cannot be performed such as Change or Cancel based on the receiver's business rules and the condition of the document. For example, the part order has already been shipped therefore the order cannot be cancelled. Type of Response Code: Error.
Required Field Missing	This occurs when one or more required fields are missing. Type of Response Code: Error.
Optional Field Missing	This occurs when one or more optional fields are missing. Type of Response Code: Warning.
Not Permitted	This code occurs when the client attempts to perform an operation that is not permitted. An example of when this may occur is if the dealer attempts to order a part when their account is placed on hold. This is to be used for authorization errors. Type of Response Code: Error.
Server Error	An error (e.g. database server is down) on the server prevented the execution of the BOD. The client will have to resend the BOD at a later time. Type of Response Code: Error.
BOD Not Supported	The received BOD or BOD version is not supported by the receiver. Type of Response Code: Error.
Invalid Structure	The structure of the BOD is not valid. For example, the BOD failed schema validation. Type of Response Code: Error.

Note

A free form note.

Name	Note
------	------

Base XSD Type: string

Reference

These field(s) use this type: **ReferenceId**.

Confirm BOD

Reference notation

Name	Reference
------	-----------

*Base XSD Type: string

ReferenceNumber

Reference number

Name	ReferenceNumber
------	-----------------

*Base XSD Type: string

ReferenceValue

These field(s) use this type: **ReferenceValue.**

The value associated with a field.

Name	ReferenceValue
------	----------------

*Base XSD Type: string

SecondaryPassword

These field(s) use this type: **SecondaryPassword.**

Secondary password used to validate access to the dealer information

Name	SecondaryPassword
------	-------------------

*Base XSD Type: string

ShortMfg

These field(s) use this type: **SenderNameCode, DestinationNameCode.**

Confirm BOD

Short Manufacturer or RSP Codes

Name	ShortMfg
------	----------

*Base XSD Type: string

SystemVersion

These field(s) use this type: SystemVersion.

The sender's software version number .

Name	SystemVersion
------	---------------

*Base XSD Type: string

Text

These field(s) use this type:

CreatorNameCode,StoreNumber,AreaNumber>Password,DestinationSoftwareCode,DestinationSoftware,StoreNumber,AreaNumber,LogicalId,Component,T

Indicates generic text type

Name	Text
------	------

*Base XSD Type: string

Type

Type

Name	Type
------	------

*Base XSD Type: string

URI

Confirm BOD

These field(s) use this type: **SenderURI, DestinationURI**.

URI

Name	URI
------	-----

*Base XSD Type: anyURI

Fields and Global Attributes

Global declarations are items such as elements, attribute groups, and group definitions. These items are not defined within any particular component. A component may reference these definitions. Within a STAR XML Schemas these are typically known as global fields.

ApplicationArea

These field(s) use this type: OriginalApplicationArea,ApplicationArea.

Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.

Provides the information that an application may need to know in order to communicate in an integration of two or more business applications. The ApplicationArea is used at the applications layer of communication. While the integration frameworks web services and middleware provide the communication layer that OAGIS operates on top of.

Name	ApplicationArea
Type	ApplicationArea
Nillable	no
Abstract	no

XML Instance Representation

```
<ApplicationArea>
  <Sender> Sender </Sender> [1]
  <CreationDateTime> DateTime </CreationDateTime> [1]
  <Signature> Signature </Signature> [0..1]
  <BODId> Code </BODId> [0..1]
  <Destination> Destination </Destination> [1]
</ApplicationArea>
```

BOD

These field(s) use this type: BOD.

Confirm BOD

The outcome of processing a specific BOD. Describes overall/summary outcome, plus the outcome of processing each noun of the BOD. Includes noun-specific error and/or warning messages encountered during processing. May include summary and/or roll-up messages at the BOD level.

Name	BOD
Type	BOD
Nilable	no
Abstract	no

XML Instance Representation

```
<BOD>
  <Header> ... </Header> [1]
  <NounOutcome> ... </NounOutcome> [0..*]
</BOD>
```

BODFailure

The processing of the BOD has failed. Provides a list of error and warning messages that explain the failure. Specific outcomes of processing each noun are reported in each of the NounOutcome elements.

Name	BODFailure
Type	ProcessingFailure
Nilable	no
Abstract	no

XML Instance Representation

```
<BODFailure>
  <ErrorMessage> ... </ErrorMessage> [0..*]
  <WarningMessage> ... </WarningMessage> [0..*]
</BODFailure>
```

BODOutcomeValue

Confirm BOD

The possible BOD-level outcomes; an extensible list.

Name	BODOutcomeValue
Type	OutcomeValue
Nilable	no
Abstract	yes

XML Instance Representation

```
<BODOutcomeValue/>
```

BODPartialSuccess

The processing of at least one noun in the BOD has failed. Error and warning messages may explain the failure. Specific outcomes of processing each noun are reported in each of the NounOutcome elements.

Name	BODPartialSuccess
Type	ProcessingFailure
Nilable	no
Abstract	no

XML Instance Representation

```
<BODPartialSuccess>  
  <ErrorMessage> ... </ErrorMessage> [0..*]  
  <WarningMessage> ... </WarningMessage> [0..*]  
</BODPartialSuccess>
```

BODSuccess

The processing of the BOD was a success. Possible, non-fatal warning messages may appear here. Specific outcomes of processing each noun are reported in each of the NounOutcome elements.

Name	BODSuccess
-------------	-------------------

Confirm BOD

Type	ProcessingSuccess
Nilable	no
Abstract	no

XML Instance Representation

```
<BODSuccess>  
  <WarningMessage> ... </WarningMessage> [0..*]  
  <SuccessMessage> ... </SuccessMessage> [0..*]  
</BODSuccess>
```

Confirm

These field(s) use this type: **Confirm**.

The Confirm verb is used to respond to a request to confirm the receipt of information by the receiving system. The request for confirmation is set by the sending application in the ApplicationArea\Sender\Confirmation field of the original BOD. The Confirm conveys the result of the original request i.e. whether or not the message was understood and was successfully processed. An example of this is Confirm BOD.

Name	Confirm
Type	Confirm
Nilable	no
Abstract	no

XML Instance Representation

```
<Confirm/>
```

ConfirmBOD

These field(s) use this type: **ConfirmBOD**.

Name	ConfirmBOD
Type	ConfirmBOD

Confirm BOD

Niltable	no
Abstract	no

XML Instance Representation

```
<ConfirmBOD
revision="Text [0..1]"
release="8.1-Lite [0..1]"
environment="Text [0..1]"
lang="Language [0..1]"
bodVersion="Text [0..1]">
  <ApplicationArea> ... </ApplicationArea> [1]
  <DataArea> ConfirmBODDataArea </DataArea> [1]
</ConfirmBOD>
```

ErrorMessage

These field(s) use this type: **ErrorMessage**.

Error message encountered during processing.

Name	ErrorMessage
Type	ErrorMessage
Niltable	no
Abstract	no

XML Instance Representation

```
<ErrorMessage>
Start Choice [1]
  <ApplicationReasonCode> ApplicationReasonCode </ApplicationReasonCode> [1]
  <Description> Description </Description> [1..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [1]
  <Description> Description </Description> [0..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [0..1]
```

Confirm BOD

End Choice

```
<ErrorType> ErrorType </ErrorType> [0..1]
<ReferenceName> ReferenceName </ReferenceName> [0..1]
<ReferenceValue> ReferenceValue </ReferenceValue> [0..1]
</ErrorMessage>
```

Header

Information about the BOD that was processed, including identifying information and a summary-level indication of the outcome of processing the BOD.

Name	Header
Type	BODHeader
Nilable	no
Abstract	no

XML Instance Representation

```
<Header>
  <DocumentDateTime> DocumentDateTime </DocumentDateTime> [0..1]
  <SecondaryPassword> SecondaryPassword </SecondaryPassword> [0..1]
  <SecondaryDealerNumber> SecondaryDealerNumber </SecondaryDealerNumber> [0..1]
  <OriginalApplicationArea> ApplicationArea </OriginalApplicationArea> [1]
  <OriginalBODReference> GenericDocumentReference </OriginalBODReference> [0..1]
  <BODOutcomeValue> ... </BODOutcomeValue> [0..1]
</Header>
```

Noun

These field(s) use this type: **Noun**.

Name	Noun
Type	Noun
Nilable	no
Abstract	yes

Confirm BOD

XML Instance Representation

```
<Noun/>
```

NounFailure

Indicates that the processing of this noun has failed, and provides error and warning messages that arose during the processing of the noun.

Name	NounFailure
Type	ProcessingFailure
Nilable	yes
Abstract	no
Business Rule	If this component is used, either the ErrorMessage or the WarningMessage component must be used.

XML Instance Representation

```
<NounFailure>  
  <ErrorMessage> ... </ErrorMessage> [0..*]  
  <WarningMessage> ... </WarningMessage> [0..*]  
</NounFailure>
```

NounOutcome

These field(s) use this type: **NounOutcome**.

Each NounOutcome captures the outcome of processing each noun of the BOD.

Name	NounOutcome
Type	NounOutcome
Nilable	no
Abstract	no

XML Instance Representation

Confirm BOD

```
<NounOutcome>
  <DocumentId> DocumentId </DocumentId> [0..1]
  <NounOutcomeValue> ... </NounOutcomeValue> [0..1]
  <DocumentDateTime> DocumentDateTime </DocumentDateTime> [0..1]
</NounOutcome>
```

NounOutcomeValue

The specific outcome of processing the noun, with supporting detail.

Name	NounOutcomeValue
Type	OutcomeValue
Nilable	no
Abstract	yes

XML Instance Representation

```
<NounOutcomeValue/>
```

NounSuccess

Indicates that the processing of this noun has succeeded; may provide non-fatal warning messages that arose during the processing of the noun.

Name	NounSuccess
Type	ProcessingSuccess
Nilable	yes
Abstract	no
Business Rule	If this component is used, either the WarningMessage or the SuccessMessage component must be used.

XML Instance Representation

```
<NounSuccess>
```

Confirm BOD

```
<WarningMessage> ... </WarningMessage> [0..*]  
<SuccessMessage> ... </SuccessMessage> [0..*]  
</NounSuccess>
```

SuccessMessage

These field(s) use this type: **SuccessMessage**.

Message indicating a success.

Name	SuccessMessage
Type	SuccessMessage
Nilable	no
Abstract	no

XML Instance Representation

```
<SuccessMessage>  
Start Choice [1]  
  <ApplicationReasonCode> ApplicationReasonCode </ApplicationReasonCode> [1]  
  <Description> Description </Description> [1..*]  
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [1]  
  <Description> Description </Description> [0..*]  
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [0..1]  
End Choice  
</SuccessMessage>
```

Verb

These field(s) use this type: **Verb**.

Name	Verb
Type	Verb
Nilable	no

Confirm BOD

Abstract	yes
-----------------	-----

XML Instance Representation

```
<Verb/>
```

WarningMessage

These field(s) use this type: WarningMessage.

Non-fatal warning message encountered during processing.

Name	WarningMessage
Type	WarningMessage
Nilable	no
Abstract	no

XML Instance Representation

```
<WarningMessage>
Start Choice [1]
  <ApplicationReasonCode> ApplicationReasonCode </ApplicationReasonCode> [1]
  <Description> Description </Description> [1..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [1]
  <Description> Description </Description> [0..*]
  <MessageReasonCode> MessageReasonCode </MessageReasonCode> [0..1]
End Choice
</WarningMessage>
```

Confirm BOD
